# SAFETY DATA SHEET

# 1. Identification

Product identifier Chockfast Versaflow Hardener

Other means of identification

SKU# GP140H

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name
Address

ITW Performance Polymers
130 Commerce Drive
Montgomeryville, PA 18936

**United States** 

**Telephone** Customer Service 215-855-8450

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number CHEMTREC 800-424-9300

International 703-527-3887

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, dermal

Skin corrosion/irritation

Serious eye damage/eye irritation

Sensitization, skin

Category 1

Category 1

Hazardous to the aquatic environment,

Category 3

Environmental hazards Hazardous to the aquatic environmental

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage.

May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long

lasting effects.

**Precautionary statement** 

**Prevention** Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face

protection.

Response Rinse mouth. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off

immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information 88.5% of the mixture consists of component(s) of unknown acute inhalation toxicity. 100% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 18.7% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name Com	nmon name and synonyms	CAS number	%
POLY(OXYPROPYLENE)DIAMINE		9046-10-0	40 - 70
2,4,6-tris-(dimethylaminomethyl)-ph enol		90-72-2	10 - 30
TRIETHYLENETETRAMINE TETA	-A	112-24-3	7 - 13
Triethylolamine		102-71-6	1 - 5

# 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

Do not use water jet as an extinguisher, as this will spread the fire.

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed. the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Chockfast Versaflow Hardener GP140H Version #: 08 Revision date: 07-27-2023 Issue date: 10-14-2019

## Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

## **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

## Precautions for safe handling

Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

## **US. ACGIH Threshold Limit Values (TLV)**

Components	Туре	Value	
Triethylolamine (CAS 102-71-6)	TWA	5 mg/m3	
US. OARS. Workplace Environme	ntal Exposure Level (WEEL) G	iuide	
Components	Туре	Value	
TRIETHYLENETETRAMIN E (CAS 112-24-3)	TWA	6 mg/m3	
		1 ppm	

## **Biological limit values**

No biological exposure limits noted for the ingredient(s).

#### **Exposure guidelines**

## **US WEEL Guides: Skin designation**

TRIETHYLENETETRAMINE (CAS 112-24-3)

Can be absorbed through the skin.

# Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles) and a face shield. Face shield is

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

## General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Material name: Chockfast Versaflow Hardener

# 9. Physical and chemical properties

**Appearance** Liquid. Liquid. Physical state **Form** Liquid.

> Color Colorless to light yellow.

Odor Ammoniacal. **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available.

Initial boiling point and boiling

212 °F (100 °C) estimated

Not available.

range

249.8 °F (121.0 °C) estimated Flash point

Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Explosive limit - lower (%) 1 % estimated 9.5 % estimated Explosive limit - upper (%) Vapor pressure 0.01 hPa estimated

Vapor density Not available. Relative density Not available.

Solubility(ies)

**Evaporation rate** 

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

561.2 °F (294 °C) estimated Auto-ignition temperature

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 0.99 g/cm3 estimated

0.95 g/cm3

Not explosive. **Explosive properties** 

Combustible IIIB estimated Flammability class

**Oxidizing properties** Not oxidizing. Specific gravity 0.99 estimated

0.95

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Contact with incompatible materials.

Peroxides. Phenols. Incompatible materials

Hazardous decomposition No hazardous decomposition products are known.

products

# 11. Toxicological information

## Information on likely routes of exposure

May cause irritation to the respiratory system. Prolonged inhalation may be harmful. Inhalation

Material name: Chockfast Versaflow Hardener

**Skin contact** Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

**Eye contact** Causes serious eye damage.

**Ingestion** Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed.

Components Species Test Results

2,4,6-tris-(dimethylaminomethyl)-phenol (CAS 90-72-2)

Acute Dermal

LD50 Rat 1280 mg/kg

Oral

LD50 Rat 1200 mg/kg

TRIETHYLENETETRAMINE (CAS 112-24-3)

Acute Dermal

Liquid

LD50 Rat 1465 mg/kg

**Oral** *Liquid* 

LD50 Rat 1716 mg/kg

Triethylolamine (CAS 102-71-6)

<u>Acute</u>

**Dermal** 

LD50 Rabbit > 20000 mg/kg

Oral

LD50 Rat 8 g/kg

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Triethylolamine (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Not classified.

repeated exposure

Material name: Chockfast Versaflow Hardener

NOT Classified

Aspiration hazard Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Triethylolamine -1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions**Dispose of this material and its container to hazardous or special waste collection point. Incinerate

the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical

or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH ≤2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

Corrosive liquids, n.o.s. (TRIETHYLENETETRAMINE)

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

UN number UN1760

UN proper shipping name

Transport hazard class(es)

Class 8
Subsidiary risk Label(s) 8
Packing group III

**Environmental hazards** 

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions 154
Packaging non bulk 203
Packaging bulk 241

IATA

UN number UN1760

**UN proper shipping name** Corrosive liquid, n.o.s. (TRIETHYLENETETRAMINE)

Transport hazard class(es)

Class 8

Subsidiary risk 
Packing group III

Environmental hazards No.

**Environmental hazards** No **ERG Code** 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Material name: Chockfast Versaflow Hardener

GP140H Version #: 08 Revision date: 07-27-2023 Issue date: 10-14-2019

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

anciait

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN number UN1760

UN proper shipping name CORROSIVE LIQUID, N.O.S. (TRIETHYLENETETRAMINE)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group III

**Environmental hazards** 

Marine pollutant No. EmS F-A, S-B

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. **nsport in bulk according to** Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

### **US** state regulations

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

# 16. Other information, including date of preparation or last revision

10-14-2019 Issue date **Revision date** 07-27-2023

Version # 08

United States & Puerto Rico

Health: 3 **HMIS®** ratings

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 1 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

**Revision information** Physical & Chemical Properties: Multiple Properties

Material name: Chockfast Versaflow Hardener

Yes