SAFETY DATA SHEET

Version #: 05

Issue date: 01-04-2020 Revision date: 09-13-2023 Supersedes date: 09-13-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

PLEXUS® MA420-AO420 EU Black Activator

Registration number

Synonyms None. SKU# IT140

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesNot available.Uses advised againstNone known.

1.3. Details of the supplier of the safety data sheet

Company Name ITW Performance Polymers

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact Person Customer Service
Telephone Number 353(61)771500

353(61)471285

Email customerservice.shannon@itwpp.com

Emergency Phone Number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center

+385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center

1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

Control Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

+45 82 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Estonia National Poisons Information Center

 $16662\ or\ abroad:\ (+372)\ 626\ 9390\ (Monday\ 9:00AM\ to\ Saturday\ 9:00AM\ (closed\ on\ Sundays\ and\ on\ national\ holidays).\ SDS/Product\ information\ may\ not\ be$

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

1.4. Emergency telephone number

Greece Poison Information

Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

aid

113

Latvia Poison and Drug Information Center

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and Emergency Department 2545 4030 (Hours of operation not provided. SDS/Product information may not be

available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC) NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intervications)

in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Portugal Poison Center 800 250 250 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center +421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Spain Toxicology Information Service

+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Organic peroxides Type F H242 - Heating may cause a fire.

Health hazards

Skin sensitization

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye irritation.

Category 1 H317 - May cause an allergic skin

reaction.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: dibenzoyl peroxide; benzoyl peroxide, Dipropylene glycol dibenzoate, Propane,

2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers, STYRENE-ETHYLENE/BUTYLENE-STYRENE

BLOCK COPOLYMER

Hazard pictograms



Signal word Warning

Hazard statements

H242	Heating may cause a fire.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Precautionary statements

			•
μ	r۵۱	/eni	ion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210 Keep only in original packaging. P234

Keep cool. P235

Ground and bond container and receiving equipment. P240

Avoid breathing mist/vapors. P261 Wash thoroughly after handling. P264

Contaminated work clothing should not be allowed out of the workplace. P272

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P280

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. P333 + P313 If eye irritation persists: Get medical advice/attention. P337 + P313 Take off contaminated clothing and wash it before reuse. P362 + P364 In case of fire: Use appropriate media to extinguish. P370 + P378

Storage

P403 Store in a well-ventilated place.

None.

Protect from sunlight. P410

Store at temperatures not exceeding 25°C / 77°F. P411

Store separately. P420

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
dibenzoyl peroxide; benzoyl peroxide	20 - < 30	94-36-0 202-327-6	-	617-008-00-0	
Classification:	Org. Perox	. B;H241, Eye Irrit. 2	;H319, Skin Sens. 1;H317		
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	20 - < 30	25085-99-8 -	-	-	
Classification:	Skin Irrit. 2	;H315, Eye Irrit. 2;H3	319, Skin Sens. 1;H317		
Dipropylene glycol dibenzoate	1 - < 3	27138-31-4 248-258-5	-	-	
Classification:	-				
STYRENE-ETHYLENE/BUTYLENE-S TYRENE BLOCK COPOLYMER	1 - < 3	66070-58-4 -	-	-	
Classification:	_				

50 - < 60 Other components below reportable

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. Composition comments

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Heating may cause a fire.

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. When using do not smoke. Keep away from clothing and other combustible materials. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Keep only in the original container. Store away from other materials.

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES (Lower-tier requirements = 50 tons; Upper-tier requirements = 200 tons)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value	Form
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	Ceiling	10 mg/m3	Inhalable fraction.
	MAK	5 mg/m3	Inhalable fraction.
Belgium. OEL. Exposure Limit Val Chemical agents, as amended	ues to Chemical Substances a	at Work, Code of Well-being	at work, Book VI, Title 1 -
Components	Туре	Value	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	TWA	5 mg/m3	
Croatia. OELs (GVI). Regulation or Biological Limit Values, Annex I (N		st Exposure to Dangerous C	hemicals at Work, OELs a
Components	Туре	Value	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	MAC	5 mg/m3	
Czech Republic. Occupational exp 361/2007, Annex 2, Part A & Annex		ls at work (Decree on protec	tion of health at work,
Components	Туре	Value	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	Ceiling	10 mg/m3	
1 (
	TWA	5 mg/m3	
		G	2
		G	2
Components dibenzoyl peroxide; benzoyl	ority. Exposure Limits for Sub	ostances & Materials, Annex	2
Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Estonia. OELs. Occupational Expo	ority. Exposure Limits for Sub Type TLV	ostances & Materials, Annex Value 5 mg/m3	
Denmark. Work Environment Auth Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Estonia. OELs. Occupational Expo Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	ority. Exposure Limits for Sub Type TLV osure Limits of Hazardous Sub	ostances & Materials, Annex Value 5 mg/m3 ostances (Regulation No. 105	
Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Estonia. OELs. Occupational Expo Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	ority. Exposure Limits for Sub Type TLV Desure Limits of Hazardous Sub Type TWA	5 mg/m3 pstances (Regulation No. 105 Value 5 mg/m3	
Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Estonia. OELs. Occupational Exponents dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Finland. HTP-arvot, App 3., Bindin	ority. Exposure Limits for Sub Type TLV Desure Limits of Hazardous Sub Type TWA	5 mg/m3 pstances (Regulation No. 105 Value 5 mg/m3	
Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Estonia. OELs. Occupational Exponents dibenzoyl peroxide; benzoyl	ority. Exposure Limits for Sub Type TLV Desure Limits of Hazardous Sub Type TWA g Limit Values, Social Affairs	5 mg/m3 pstances (Regulation No. 105 Value 5 mg/m3 and Ministry of Health	
Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Estonia. OELs. Occupational Exponents dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Finland. HTP-arvot, App 3., Bindin Components dibenzoyl peroxide; benzoyl	ority. Exposure Limits for Sub Type TLV Desure Limits of Hazardous Sub Type TWA g Limit Values, Social Affairs Type	ostances & Materials, Annex Value 5 mg/m3 ostances (Regulation No. 105 Value 5 mg/m3 and Ministry of Health Value	
Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Estonia. OELs. Occupational Exponents dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Finland. HTP-arvot, App 3., Bindin Components dibenzoyl peroxide; benzoyl	ority. Exposure Limits for Sub Type TLV Desure Limits of Hazardous Sub Type TWA g Limit Values, Social Affairs Type STEL TWA	5 mg/m3 stances (Regulation No. 105 Value 5 mg/m3 and Ministry of Health Value 10 mg/m3 5 mg/m3	5/2001, Annex), as amende

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds

Type TWA Value

5 mg/m3

Form

Inhalable fraction.

Material name: PLEXUS® MA420-AO420 EU Black Activator

in the Work Area (DFG), as updated

dibenzoyl peroxide; benzoyl

peroxide (CAS 94-36-0)

Components

SDS EU

IT140 Version #: 05 Revision date: 09-13-2023 Issue date: 01-04-2020

	Туре	Value	Form
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	AGW	5 mg/m3	Inhalable fraction.
Greece. OELs, Presidential Decree Components	No. 307/1986, as amended Type	Value	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	TWA	5 mg/m3	
Hungary. OELs. Decree on protect Components	ion of workers exposed to che Type	emical agents (5/2020. (II.6)) Value	, Annex 1&2, as amended
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	STEL	5 mg/m3	
, , ,	TWA	5 mg/m3	
celand. OELs. Regulation 390/200 Components	9 on Pollution Limits and Mea Type	sures to Reduce Pollution a Value	t the Workplace, as amend
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	TWA	5 mg/m3	
reland. OELVs, Schedules 1 & 2, C Components	Code of Practice for Chemical Type	Agents and Carcinogens Ro Value	egulations
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	TWA	5 mg/m3	
taly. OELs (Legislative Decree n.8 Components	1, 9 April 2008), as amended Type	Value	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	TWA	5 mg/m3	
Norway. Regulation No. 1358 on M Infection Groups for Biological Fac	ctors, as amended	Physical and Chemical Fact	ors in Work Environment a
Components	Type	Value	
<u> </u>	Type TLV	Value 5 mg/m3	
dibenzoyl peroxide; benzoyl		Value 5 mg/m3	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con	TLV	5 mg/m3	environment (Dz.U.Poz.
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1)	TLV	5 mg/m3	environment (Dz.U.Poz.
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1) Components dibenzoyl peroxide; benzoyl	TLV centrations and intensities of	5 mg/m3	environment (Dz.U.Poz.
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1) Components dibenzoyl peroxide; benzoyl	TLV centrations and intensities of	5 mg/m3 harmful factors in the work Value	environment (Dz.U.Poz.
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1) Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Portugal. VLEs. Norm on occupation	TLV centrations and intensities of Type STEL TWA	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3	environment (Dz.U.Poz.
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1) Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Portugal. VLEs. Norm on occupation components dibenzoyl peroxide; benzoyl peroxide; benzoyl peroxide (CAS 94-36-0)	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014)	environment (Dz.U.Poz.
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1) Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Portugal. VLEs. Norm on occupation components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Slovakia. OELs. Maximum permissible con 1286/2018	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1) Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Portugal. VLEs. Norm on occupation occup	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible continuous (Cas 94-36-0) Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Portugal. VLEs. Norm on occupation (Cas 94-36-0) dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Slovakia. OELs. Maximum permission (Cas 94-36-0) Slovakia. OELs. Maximum permission (Cas 94-36-0) Components dibenzoyl peroxide; benzoyl (Cas 94-36-0)	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA sible exposure limits for chem	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3 ical factors in workplace air	
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible continuous (CAS 94-36-0) Poland. Maximum permissible continuous (CAS 94-36-0) Portugal. VLEs. Norm on occupation (CAS 94-36-0) Portugal. VLEs. Norm on occupation (CAS 94-36-0) Slovakia. OELs. Maximum permissible components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Slovakia. OELs. Maximum permissible components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Slovenia. OELs. Occupational Expidue to Exp. to Chemicals at Work,	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA sible exposure limits for chem Type TWA osure Limits of Chemicals at V	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3 ical factors in workplace air Value 5 mg/m3 Vorkplace (Reg. on Protecti	(Regulation No 355/2006,
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible continuous (CAS 94-36-0) Poland. Maximum permissible continuous (CAS 94-36-0) Portugal. VLEs. Norm on occupation (CAS 94-36-0) Portugal. VLEs. Norm on occupation (CAS 94-36-0) Slovakia. OELs. Maximum permissible components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Slovakia. OELs. Maximum permissible components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Slovenia. OELs. Occupational Expidue to Exp. to Chemicals at Work,	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA sible exposure limits for chem Type TWA osure Limits of Chemicals at V	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3 ical factors in workplace air Value 5 mg/m3	(Regulation No 355/2006,
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible con 1286/2018, Annex 1) Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Portugal. VLEs. Norm on occupation occupa	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA sible exposure limits for chem Type TWA osure Limits of Chemicals at V	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3 ical factors in workplace air Value 5 mg/m3 Vorkplace (Reg. on Protecti	(Regulation No 355/2006,
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible continuous (Cas 94-36-0) Poland. Maximum permissible continuous (Cas 94-36-0) Portugal. VLEs. Norm on occupation (Cas 94-36-0) Portugal. VLEs. Norm on occupation (Cas 94-36-0) Slovakia. OELs. Maximum permissible (Cas 94-36-0) Slovakia. OELs. Maximum permissible (Cas 94-36-0) Slovakia. OELs. Occupational Exputation (Cas 94-36-0) Slovenia. OELs. Occupational Exputation (Cas 94-36-0) Slovenia. OELs. Occupational Exputation (Cas 94-36-0) Spain. OELs. INSST, Límites de Expain.	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA sible exposure limits for chem Type TWA osure Limits of Chemicals at V Annex I), as amended Type TWA	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3 ical factors in workplace air Value 5 mg/m3 Workplace (Reg. on Protection Value 5 mg/m3	r (Regulation No 355/2006, ion of Workers from Risks Form Inhalable fraction.
dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Poland. Maximum permissible contents (CAS 94-36-0) Components dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Portugal. VLEs. Norm on occupation (CAS 94-36-0) Portugal. VLEs. Norm on occupation (CAS 94-36-0) Slovakia. OELs. Maximum permiss (CAS 94-36-0) Slovakia. OELs. Maximum permiss (CAS 94-36-0) Slovakia. OELs. Maximum permiss (CAS 94-36-0) Slovakia. OELs. Occupational Experioride (CAS 94-36-0) Slovenia. OELs. Occupational Experioride (CAS 94-36-0) Spain. OELs. INSST, Límites de Experioride (CAS 94-36-0) Spain. OELs. INSST, Límites de Exponents (VLAS) Components	TLV centrations and intensities of Type STEL TWA conal exposure to chemical age Type TWA sible exposure limits for chem Type TWA osure Limits of Chemicals at V Annex I), as amended Type TWA	5 mg/m3 harmful factors in the work Value 10 mg/m3 5 mg/m3 ents (NP 1796-2014) Value 5 mg/m3 ical factors in workplace air Value 5 mg/m3 Workplace (Reg. on Protection Value 5 mg/m3	r (Regulation No 355/2006, ion of Workers from Risks Form Inhalable fraction.

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte Form Components Value Type dibenzoyl peroxide; benzoyl **STEL** 5 mg/m3 Inhalable fraction. peroxide (CAS 94-36-0) **TWA** 5 mg/m3 Inhalable fraction. UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1 Components Value Type TWA dibenzoyl peroxide; benzoyl 5 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring

peroxide (CAS 94-36-0)

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

Exposure guidelines

Hungary OELs: Skin designation

dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

> after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid.

Form Viscous. Liquid. Color Natural color. Odor Slight.

217,4 °F (103 °C) estimated Melting point/freezing point **Boiling point or initial boiling** 608 °F (320 °C) estimated point and boiling range

Not applicable. **Flammability**

265,0 °F (129,4 °C) estimated Flash point 176 °F (80 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available.

pН

Kinematic viscosity Not available.

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapor pressure -0,001 hPa estimated

Density and/or relative density

Density 1,16 g/cm3 estimated

Vapor density Not available.

Particle characteristics Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Specific gravity 1,16 estimated

VOC <20 g/l Mixed components

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Sunlight. Contact with incompatible

materials.

10.5. Incompatible materials Acids. Strong oxidizing agents. Combustible material. Alcohols. Amines.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Components Species Test Results

dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)

<u>Acute</u>

Oral

LD50 Rat 7710 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory sensitizationDue to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

dibenzoyl peroxide; benzoyl peroxide (CAS 94-36-0)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. ToxicityBased on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

3.46

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

dibenzoyl peroxide; benzoyl peroxide

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Special precautionsDispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -

Hazard No. (ADR) Not assigned.

Tunnel restriction code Not assigned.

14.4. Packing group - **14.5. Environmental hazards** No.

14.6. Special precautions Not assigned.

for user

RID

14.1. UN number Not regulated as dangerous goods. 14.2. UN proper shipping Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

ADN

Not regulated as dangerous goods. 14.1. UN number 14.2. UN proper shipping Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IATA

14.1. UN number UN3082

14.2. UN proper shipping Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

name

14.3. Transport hazard class(es)

Class 9 Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Yes **ERG Code** 91

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin), MARINE

name POLLUTANT

14.3. Transport hazard class(es)

9 Class Subsidiary risk Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant Yes F-A, S-F **EmS**

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.


for user **Epoxy Resin**

14.7. Maritime transport in bulk

Not established.

according to IMO instruments

IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended. Follow national

regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

France regulations

France INRS Table of Occupational Diseases

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers Maladies professionnelles provoquées par les résines (CAS 25085-99-8) époxydiques et leurs constituants 51

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H241 Heating may cause a fire or explosion.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: PLEXUS® MA420-AO420 EU Black Activator

IT140 Version #: 05 Revision date: 09-13-2023 Issue date: 01-04-2020 12 / 12

SDS FII