SAFETY DATA SHEET

1. Identification

Address

Product identifier ITW PRC 100 Grout

Other means of identification

SKU# GP111A

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

35 Brownridge Road

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number215-855-8450Fax number215-855-4688

Emergency Number 800-424-9300 (CHEMTREC)

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A

Specific target organ toxicity following single

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious

eye damage. May cause respiratory irritation. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.

Category 3 respiratory tract irritation

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth. IF ON SKIN: Response

Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it

before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information 99.8 % of the mixture consists of component(s) of unknown acute oral toxicity. 99.8 % of the

mixture consists of component(s) of unknown acute dermal toxicity. 99.8 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 99.8 % of the mixture

consists of component(s) of unknown long-term hazards to the aquatic environment.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Portland Cement		65997-15-1	30 - 60
Quartz		14808-60-7	30 - 60
Fly Ash		68131-74-8	5 - 15
Limestone		1317-65-3	5 - 15
Naphthalene		91-20-3	< 0.4

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison Inhalation

centre or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed **General information** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis, Rash.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH	Threshold Limit	Values	(TLV)

Components	Туре	Value	Form
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	
Naphthalene (CAS 91-20-3)	STEL	79 mg/m3	
		15 ppm	
	TWA	52 mg/m3	
		10 ppm	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Material name: ITW PRC 100 Grout SDS CANADA

GP111A Version #: 01 Issue date: 17-August-2023

	Туре	Value	Form
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Canada. New Brunswick OELs: Thr Publication (New Brunswick Regula		(TLVs) Based on the 1991 and 1997 AC	CGIH TLVs and BEIs
Components	Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	3 mg/m3	Respirable.
		10 mg/m3	Inhalable
Naphthalene (CAS 91-20-3)	STEL	79 mg/m3	
		15 ppm	
	TWA	52 mg/m3	
		10 ppm	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
Canada. Ontario OELs. (Control of l Components	Exposure to Biologic Type	al or Chemical Agents), as amended Value	Form
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Canada. Quebec OELs. (Ministry of Components	Labor - Regulation r Type	especting occupational health and sat Value	ety), as amended Form
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	Total dust.
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
	=	Safety Regulations, 1996, Table 21), a Value	s amended
	Туре	Value	
Components	Type 15 minute	20 mg/m3	
Components Limestone (CAS 1317-65-3)			
Components Limestone (CAS 1317-65-3)	15 minute	20 mg/m3	
Components Limestone (CAS 1317-65-3) Naphthalene (CAS 91-20-3) Portland Cement (CAS	15 minute 15 minute	20 mg/m3 15 ppm	
Components Limestone (CAS 1317-65-3) Naphthalene (CAS 91-20-3) Portland Cement (CAS 65997-15-1) ogical limit values osure guidelines Occup	15 minute 15 minute 8 hour 15 minute	20 mg/m3 15 ppm 10 ppm 20 mg/m3 s noted for the ingredient(s). uisance dust (total and respirable) and re-	spirable crystalline silica
Components Limestone (CAS 1317-65-3) Naphthalene (CAS 91-20-3) Portland Cement (CAS 65997-15-1) ogical limit values osure guidelines No bic Occup	15 minute 15 minute 8 hour 15 minute blogical exposure limits bational exposure to nu	20 mg/m3 15 ppm 10 ppm 20 mg/m3 s noted for the ingredient(s). uisance dust (total and respirable) and re-	spirable crystalline silica
Components Limestone (CAS 1317-65-3) Naphthalene (CAS 91-20-3) Portland Cement (CAS 65997-15-1) ogical limit values osure guidelines Canada - Alberta OELs: Skin design Naphthalene (CAS 91-20-3)	15 minute 15 minute 8 hour 15 minute blogical exposure limits bational exposure to number of the monitored and connation	20 mg/m3 15 ppm 10 ppm 20 mg/m3 s noted for the ingredient(s). uisance dust (total and respirable) and re-	spirable crystalline silica
Components Limestone (CAS 1317-65-3) Naphthalene (CAS 91-20-3) Portland Cement (CAS 65997-15-1) ogical limit values osure guidelines Canada - Alberta OELs: Skin design Naphthalene (CAS 91-20-3) Canada - British Columbia OELs: S Naphthalene (CAS 91-20-3)	15 minute 15 minute 8 hour 15 minute blogical exposure limits bational exposure to number of the monitored and connation kin designation	20 mg/m3 15 ppm 10 ppm 20 mg/m3 s noted for the ingredient(s). uisance dust (total and respirable) and rentrolled.	spirable crystalline silica
Components Limestone (CAS 1317-65-3) Naphthalene (CAS 91-20-3) Portland Cement (CAS 65997-15-1) ogical limit values osure guidelines Canada - Alberta OELs: Skin design Naphthalene (CAS 91-20-3) Canada - British Columbia OELs: S	15 minute 15 minute 8 hour 15 minute loogical exposure limits pational exposure to number of the monitored and connation kin designation ignation	20 mg/m3 15 ppm 10 ppm 20 mg/m3 s noted for the ingredient(s). uisance dust (total and respirable) and rentrolled. Can be absorbed through the skin.	spirable crystalline silica

Material name: ITW PRC 100 Grout

SDS CANADA

Canada - Quebec OELs: Skin designation

Naphthalene (CAS 91-20-3) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Can be absorbed through the skin.

Naphthalene (CAS 91-20-3)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Naphthalene (CAS 91-20-3) Danger of cutaneous absorption

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid.
Colour Grey
Odour Slightly.
Odour threshold Not available.
pH Not available.

Melting point/freezing point 1200 °C (2192 °F) estimated

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure

-0.01 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 2.60 - 3.20 g/cm3

Explosive properties Not explosive.

Oxidising properties Not oxidising.

Specific gravity 2.6 - 3.2

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Acids. Powerful oxidizers. Chlorine. Fluorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

Naphthalene (CAS 91-20-3)

Acute

Dermal

LD50 Rabbit > 2 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Limestone (CAS 1317-65-3) Irritant
Portland Cement (CAS 65997-15-1) Irritant

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

ACGIH Carcinogens

Naphthalene (CAS 91-20-3)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Portland Cement (CAS 65997-15-1) A4 Not classifiable as a human carcinogen.

Quartz (CAS 14808-60-7) A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

Quartz (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Naphthalene (CAS 91-20-3) Confirmed animal carcinogen with unknown relevance to humans.

Portland Cement (CAS 65997-15-1) Not classifiable as a human carcinogen.

Quartz (CAS 14808-60-7) Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

Naphthalene (CAS 91-20-3)

Quartz (CAS 14808-60-7)

Detected carcinogenic effect in animals.

Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Naphthalene (CAS 91-20-3) 2B Possibly carcinogenic to humans.

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Naphthalene (CAS 91-20-3) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of any ingredients in the mixture.

Persistence and degradability No data is available

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Naphthalene 3.3

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

Inventory name

Naphthalene (CAS 91-20-3)

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Naphthalene (CAS 91-20-3)

International Inventories

Country(s) or region

Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Material name: ITW PRC 100 Grout SDS CANADA

On inventory (yes/no)*

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 17-August-2023

Version No. 01

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Product and Company Identification: Product and Company Identification

Hazard identification: Hazard statement Hazard identification: Prevention

Composition / Information on Ingredients: Disclosure Overrides

First-aid measures: Most important symptoms/effects, acute and delayed

Toxicological information: Chronic effects

Toxicological information: Specific target organ toxicity - repeated exposure

Toxicological information: Symptoms related to the physical, chemical and toxicological

characteristics GHS: Classification