



Prolong the Life of Primary & Secondary Crushers Protect Against Shock Impact & Vibrations







Devcon Korrobond 65 is a high performance backing compound for use in rock crushing equipment including gyratory and cone crushers. This proven shock absorbing compound extends the life of crusher equipment by preventing common issues such as leaks, corrosion, and loosening thereby increasing plant productivity.

The Devcon Korrobond 65 two component epoxy is specially formulated to produce a low viscosity, tough yet flexible backing compound. It serves as a backing and reinforcing layer between machine parts, absorbs and dampens impact of the liner to the crusher, and serves as a damper when subject to impact and shock vibrations.

Extends Equipment Life

- Superior gap filling properties
- Very high compressive strength 135 +/- 7 MPa (19,500 +/- 1000 psi)
- Outstanding resilienceMinimal shrinkage
- Easy to Use
- 100% solids, no solvents
- · Easy to mix and pour

Devcon Korrobond's overall quality is unrivalled in the industry, ensuring equipment is operating at peak performance in all climates, resulting in improved plant productivity.



Korrobond 65 Crusher Backing Compound



| Typical Properties | |
|---------------------------|-------------------------------------|
| Adhesive Lap Shear | > 354 Kg/m² |
| Color | Light Gray |
| Compressive Strength | 135 +/- 7 MPa (19,500 +/- 1000 psi) |
| Adhesive Tensile Strength | > 27MPa / 4,000 psi |
| Cured Shrinkage | 0.01% |
| Functional Cure | 8 - 10 Hours |
| Mix Ratio by Volume | 7 Resin : 1 Hardener |
| Mix Ratio by Weight | 13.3 : 1.0 |
| Mixed Viscosity | > 20,000 CPs |
| Pot Life @ 23°C / 73°F | 15 - 20 minutes |
| Solids by Volume | 100% |

Packaging

| Item no. | Product - Component | Volume |
|----------|-------------------------|----------------|
| 81065 | Devcon Korrobond 65 Kit | 10 kg / 22 lbs |
| 81070 | Devcon Korrobond 65 Kit | 20 kg / 44 lbs |

Proven Solution

Devcon Korrobond 65 high-performance backing compound ensures machinery runs as long as possible before replacing worn parts and has demonstrated time and again to improve overall productivity in all climates.

Refer to our Technical Data Sheet and Safety Data Sheet for additional technical and safety information

The technical information, recommendations and other statements contained in this sheet are based upon good faith tests or experience that ITW Performance Polymers believes are reliable, but the accuracy or completeness of such information is not guaranteed. The information is not intended to substitute for the customers' own testing.