SAFETY DATA SHEET

Version #: 02

Issue date: 07-24-2023 Revision date: 09-09-2023 Supersedes date: 07-24-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Devweld 531 Activator

Registration number

Synonyms None.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers Company name

Address Bay 150

Shannon Industrial Estate

Co. Clare, Ireland

Division

Telephone Phone 353(61)771500

e-mail customerservice.shannon@itwpp.com

Not available. Contact person

1.4. Emergency telephone

number

44(0)1235 239 670 **Emergency Number**

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day, SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons Information Center +385 1 2348 342 (Hours of operation not provided. SDS/Product information may

not be available for the Emergency Service.)

1401 (Available 24 hours a day. SDS/Product information may not be available **Cyprus Poison Center**

for the Emergency Service.)

Czech Republic National

Poisons Information Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Greece Poison Information Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

Material name: Devweld 531 Activator

be available for the Emergency Service.)

SDS FII

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Iceland Poison Center

(+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

113

Latvia Emergency medical

Latvia Poison and Drug +371 67042473 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.) Information Center

Lithuania Neatidėliotina informacija apsinuodijus

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department** 2545 4030 (Hours of operation not provided. SDS/Product information may not be

available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel

in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Romania Biroul RSI si

021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

Informare Toxicologica **Slovakia National**

available for the Emergency Service.)

Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Spain Toxicology Information Service + 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapor.

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Skin sensitization Category 1 H317 - May cause an allergic skin

reaction.

Specific target organ toxicity - single

exposure

Category 3 respiratory tract irritation

H335 - May cause respiratory

irritation.

2.2. Label elements

Material name: Devweld 531 Activator 4451 Version #: 02 Revision date: 09-09-2023 Issue date: 07-24-2023

SDS FII

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: 0DG0-F0CK-D00A-7VE7 Belgium: 0DG0-F0CK-D00A-7VE7 Bulgaria: 0DG0-F0CK-D00A-7VE7 Croatia: 0DG0-F0CK-D00A-7VE7 Cyprus: 0DG0-F0CK-D00A-7VE7

Czech Republic: 0DG0-F0CK-D00A-7VE7
Denmark: 0DG0-F0CK-D00A-7VE7
Estonia: 0DG0-F0CK-D00A-7VE7
EU: 0DG0-F0CK-D00A-7VE7
Finland: 0DG0-F0CK-D00A-7VE7
France: 0DG0-F0CK-D00A-7VE7
Germany: 0DG0-F0CK-D00A-7VE7
Greece: 0DG0-F0CK-D00A-7VE7
Hungary: 0DG0-F0CK-D00A-7VE7
Iceland: 0DG0-F0CK-D00A-7VE7
Ireland: 0DG0-F0CK-D00A-7VE7
Italy: 0DG0-F0CK-D00A-7VE7
Latvia: 0DG0-F0CK-D00A-7VE7
Lithuania: 0DG0-F0CK-D00A-7VE7

Lithdania. 0DG0-F0CK-D00A-7VE7
Luxembourg: 0DG0-F0CK-D00A-7VE7
Malta: 0DG0-F0CK-D00A-7VE7
Netherlands: 0DG0-F0CK-D00A-7VE7
Norway: 0DG0-F0CK-D00A-7VE7
Poland: 0DG0-F0CK-D00A-7VE7
Portugal: 0DG0-F0CK-D00A-7VE7
Romania: 0DG0-F0CK-D00A-7VE7
Slovakia: 0DG0-F0CK-D00A-7VE7
Slovenia: 0DG0-F0CK-D00A-7VE7

Spain: 0DG0-F0CK-D00A-7VE7 Sweden: 0DG0-F0CK-D00A-7VE7

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

Hazard pictograms

Contains:





Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapors.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

Store locked up. P405

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

80% of the mixture consists of component(s) of unknown acute inhalation toxicity. 80% of the Supplemental label information

mixture consists of component(s) of unknown acute hazards to the aquatic environment. 80% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	60-100%	80-62-6 201-297-1	01-2119452498-28-0000	607-035-00-6	#
Classification	1: Flam. Liq. 2 3;H335	2;H225, Skin Irrit. 2;F	H315, Skin Sens. 1;H317, S	TOT SE	

Other components below reportable

levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

Specific Concentration Limits: STOT SE 3;H335: C ≥ 10 %

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. **Composition comments**

SECTION 4: First aid measures

General information Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the

label where possible). Ensure that medical personnel are aware of the material(s) involved, and

take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Direct contact with eyes may cause temporary irritation. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapor.

5.1. Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Specific methods

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Avoid discharge into drains, water courses or onto the ground.

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tons; Upper-tier requirements = 200 tons)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ord	inance (GwV), BGBI. II, no. 184/2001, as amende	ed
Components	Туре	

methyl methacrylate; methyl Ceiling 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

420 mg/m3

Value

MAK 210 mg/m3

50 ppm

Material name: Devweld 531 Activator
4451 Version #: 02 Revision date: 09-09-2023 Issue date: 07-24-2023

Belgium. OEL. Exposure Limit Values to Chemical Substances at World	k, Code of Well-being at work, Book VI, Title 1 -
Chemical agents, as amended	

Туре	Value	
STEL	416 mg/m3	
	100 ppm	
TWA	208 mg/m3	
	50 ppm	
		STEL 416 mg/m3 100 ppm TWA 208 mg/m3

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	MAC	50 ppm	
	STEL	100 ppm	

Cyprus. OELs. Occupational Exposure Limit Values of Chemicals at Work (Safety and Health at Work (Chem. Agents) Reg., Ann. 1, R.A.A. 268/2001, as amended)

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	150 mg/m3	
	TWA	50 mg/m3	

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2 Components Value

Components	туре	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TLV	102 mg/m3
		25 nnm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended Components Value

Components	Type	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

nyl STEL te	210 mg/m3	
	50 ppm	
TWA	· ·	
	10 ppm	
onal Exposure Limits as Prescribed by Ar Type	t. R.4412-149 of Labor Code, as amended Value	
nyl VLE te	410 mg/m3	
	100 ppm	
VME	205 mg/m3	
	50 ppm	
Values (VLEP) for Occupational Exposur Type	e to Chemicals in France, INRS ED 984 Value	
nyl VLE te	410 mg/m3	
Regulatory binding (VRC)	400	
	100 ppm	
	205 ma/m3	
	203 mg/m3	
regulatory binding (vite)	50 ppm	
Regulatory binding (VRC)	•	
	estigation of Health Hazards of Chemical Compo	unds
Туре	Value	
nyl TWA te	210 mg/m3	
	50 ppm	
<u> </u>		
nyl AGW te	210 mg/m3	
	50 ppm	
tial Decree No. 307/1986, as amended Type	Value	
••		
nyl STEL te	100 ppm	
	Type nyl VLE te VME Values (VLEP) for Occupational Exposure Type nyl VLE te Regulatory binding (VRC) VME Regulatory binding (VRC) VME Regulatory binding (VRC) t (advisory OELs). Commission for the Invasu updated Type nyl TWA te nit Values in the Ambient Air at the Workp Type nyl AGW	onal Exposure Limits as Prescribed by Art. R.4412-149 of Labor Code, as amended Type Value Type Value 100 ppm 100 ppm VME 205 mg/m3 50 ppm Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Type Value 100 ppm Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 Type Value 100 ppm Value 410 mg/m3 Regulatory binding (VRC) 100 ppm Regulatory binding (VRC) VME 205 mg/m3 Regulatory binding (VRC) 50 ppm Regulatory binding (VRC) t (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Composas updated Type Value 100 ppm 100

Material name: Devweld 531 Activator

4451 Version #: 02 Revision date: 09-09-2023 Issue date: 07-24-2023 7 / 17

Components	Туре	445 manulas 2
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	415 mg/m3
	TWA	208 mg/m3
celand. OELs. Regulation 390/2009 Components	on Pollution Limits and Me Type	asures to Reduce Pollution at the Workplace, as amended Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm
ireland. OELVs, Schedules 1 & 2, C Components		l Agents and Carcinogens Regulations Value
•	Type STEL	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	SIEL	100 ppm
,	TWA	50 ppm
Italy. OELs (Legislative Decree n.8		
Components	Туре	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm
	ure Limits of Chemical Subs	tances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex
1), as amended Components	Туре	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	TWA	10 mg/m3
	osure Limit Values for Chen	nical Substances (Hygiene Norm HN 23:2011; Order No.
V-824/A1-389), as amended Components	Туре	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	STEL	416 mg/m3
(CAS 80-62-6)		400
	TIA/A	100 ppm
	TWA	208 mg/m3
Luvenskaum OFLa Binding Occur	antiamal Europeuma Limit Vale	50 ppm
n ° 235/2016, as amended	pational Exposure Limit valu	ues (Annex I), G.D.R. of 14 November 2016, OJ Memorial A
Components	Туре	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
-/	TWA	50 ppm
	and Safety of Workers from F	Risks related to Chemical Agents at Work (L.N 227/2003
Schedules I and V), as amended	Туре	Value
Components		Tuluo
Components methyl methacrylate; methyl	STEL	100 ppm

Components	Туре	Value
	TWA	50 ppm

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Components	Type	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	410 mg/m3	
	TWA	205 mg/m3	

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	400 mg/m3	
		100 ppm	
	TLV	100 mg/m3	
		25 ppm	

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	300 mg/m3	
	TWA	100 mg/m3	

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)

Components	туре	value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

Components	Type	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	410 mg/m3	
		100 ppm	
	TWA	205 mg/m3	
		50 ppm	

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Туре	Value
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended Components Type Walue methyl methacrylate; methyl TWA 210 mg/m3 2-methylprop-2-enoate;

Spain. OELs. I	NSST, Límites de	Exposición Profesi	onal Para Agentes Químicos	, Table 1-Valores Límites	Ambientales
(VI As)		-	_		

50 ppm

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	Ceiling	400 mg/m3	
		100 ppm	
	TWA	200 mg/m3	
		50 ppm	

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Туре	Value	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	420 mg/m3	
		100 ppm	
	TWA	210 mg/m3	
		50 ppm	

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1 Components Type Value

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m3
		100 ppm
	TWA	208 mg/m3
		50 ppm

STEL

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU Components Type Value

methyl methacrylate; methyl
2-methylprop-2-enoate;
methyl 2-methylpropenoate
(CAS 80-62-6)

methyl 2-methylpropenoate

(CAS 80-62-6)

TWA 50 ppm

100 ppm

Biological limit valuesNo biological exposure limits noted for the ingredient(s). **Recommended monitoring procedures Follow standard monitoring procedures.**

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

Exposure guidelines

Croatia ELVs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;

methyl 2-methylpropenoate (CAS 80-62-6)

Denmark GV: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;

methyl 2-methylpropenoate (CAS 80-62-6)

Hungary OELs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;

methyl 2-methylpropenoate (CAS 80-62-6)

Iceland OELs: Skin designation

methyl methacrylate; methyl 2-methylprop-2-enoate;

methyl 2-methylpropenoate (CAS 80-62-6)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General informationUse personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.
 - Other Wear appropriate chemical resistant clothing.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.FormLiquid.ColorYellow

Odor Slight. Pungent

Melting point/freezing point -54,4 °F (-48 °C) estimated

Boiling point or initial boiling

point and boiling range

213,8 °F (101 °C)

Flammability Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 2,1 % estimated
Explosive limit - upper (%) 8,2 % estimated
Flash point 50,0 °F (10,0 °C)

Auto-ignition temperature 815 °F (435 °C) estimated

Decomposition temperature Not available. pH 4,5 - 5,5

Kinematic viscosity 0,042 - 0,073 m²/s

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapor pressure 28 mm Hg

Density and/or relative density

Density 0,96 g/cm3 Vapor density Not available. Not available. Particle characteristics

9.2. Other information

9.2.1. Information with regard No relevant additional information available.

to physical hazard classes

9.2.2. Other safety characteristics Specific gravity 0.96

> VOC <50 g/I Mixed components

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. 10.2. Chemical stability

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidizing agents. Nitrates. Peroxides.

10.6. Hazardous decomposition products No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

May cause irritation to the respiratory system. Prolonged inhalation may be harmful. Inhalation

Skin contact Causes skin irritation. May cause an allergic skin reaction. Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an

allergic skin reaction. Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not known.

Test Results Components **Species**

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

Acute Oral

LD50 Rat 7800 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

methyl methacrylate: methyl 2-methylprop-2-enoate: 3 Not classifiable as to carcinogenicity to humans.

methyl 2-methylpropenoate (CAS 80-62-6)

Due to partial or complete lack of data the classification is not possible. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Material name: Devweld 531 Activator

SDS FU 4451 Version #: 02 Revision date: 09-09-2023 Issue date: 07-24-2023

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. ToxicityBased on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 1,38

2-methylpropenoate

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

12.7. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Special precautionsDispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1133

14.2. UN proper shipping

ADHESIVES containing flammable liquid (vapour pressure at 50 °C more than 110 kPa)

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Hazard No. (ADR) 33
Tunnel restriction code D/E
14.4. Packing group ||

14.5. Environmental hazards No.

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid (having a flash-point below 23 °C and viscous

name according to 2.2.3.1.4) (vapour pressure at 50 °C more than 110 kPa)

Material name: Devweld 531 Activator
4451 Version #: 02 Revision date: 09-09-2023 Issue date: 07-24-2023

14.3. Transport hazard class(es)

Subsidiary risk Label(s) 3

14.4. Packing group | II

14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
14.4. Packing group II
14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1133

14.2. UN proper shipping Adhesives containing flammable liquid

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk
14.4. Packing group II

14.5. Environmental hazards No.
ERG Code 3L

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid

name

14.3. Transport hazard class(es)

Class 3
Subsidiary risk
14.4. Packing group II

14.5. Environmental hazards

Marine pollutant No.

EmS F-E, S-D

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments

Not established.

according to IMO instruments



4451 Version #: 02 Revision date: 09-09-2023 Issue date: 07-24-2023

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

UFI:

Austria: 0DG0-F0CK-D00A-7VE7 Belgium: 0DG0-F0CK-D00A-7VE7 Bulgaria: 0DG0-F0CK-D00A-7VE7 Croatia: 0DG0-F0CK-D00A-7VE7 Cyprus: 0DG0-F0CK-D00A-7VE7

Czech Republic: 0DG0-F0CK-D00A-7VE7 Denmark: 0DG0-F0CK-D00A-7VE7 Estonia: 0DG0-F0CK-D00A-7VE7 EU: 0DG0-F0CK-D00A-7VE7 Finland: 0DG0-F0CK-D00A-7VE7 France: 0DG0-F0CK-D00A-7VE7 Germany: 0DG0-F0CK-D00A-7VE7 Greece: 0DG0-F0CK-D00A-7VE7 Hungary: 0DG0-F0CK-D00A-7VE7 Iceland: 0DG0-F0CK-D00A-7VE7 Ireland: 0DG0-F0CK-D00A-7VE7 Italy: 0DG0-F0CK-D00A-7VE7 Latvia: 0DG0-F0CK-D00A-7VE7 Lithuania: 0DG0-F0CK-D00A-7VE7 Luxembourg: 0DG0-F0CK-D00A-7VE7 Malta: 0DG0-F0CK-D00A-7VE7 Netherlands: 0DG0-F0CK-D00A-7VE7 Norway: 0DG0-F0CK-D00A-7VE7 Poland: 0DG0-F0CK-D00A-7VE7 Portugal: 0DG0-F0CK-D00A-7VE7 Romania: 0DG0-F0CK-D00A-7VE7 Slovakia: 0DG0-F0CK-D00A-7VE7

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Slovenia: 0DG0-F0CK-D00A-7VE7 Spain: 0DG0-F0CK-D00A-7VE7 Sweden: 0DG0-F0CK-D00A-7VE7

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

France regulations

France INRS Table of Occupational Diseases

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

Affections provoquées par le méthacrylate de méthyle 82

Product registration number

UFI: 0DG0-F0CK-D00A-7VE7 **Austria Belgium** UFI: 0DG0-F0CK-D00A-7VE7 **Czech Republic** UFI: 0DG0-F0CK-D00A-7VE7 Denmark UFI: 0DG0-F0CK-D00A-7VE7 **European Union** UFI: 0DG0-F0CK-D00A-7VE7 UFI: 0DG0-F0CK-D00A-7VE7 **Finland** UFI: 0DG0-F0CK-D00A-7VE7 France UFI: 0DG0-F0CK-D00A-7VE7 Germany UFI: 0DG0-F0CK-D00A-7VE7 Greece UFI: 0DG0-F0CK-D00A-7VE7 Hungary Italy UFI: 0DG0-F0CK-D00A-7VE7 **Netherlands** UFI: 0DG0-F0CK-D00A-7VE7 UFI: 0DG0-F0CK-D00A-7VE7 **Norway Poland** UFI: 0DG0-F0CK-D00A-7VE7 UFI: 0DG0-F0CK-D00A-7VE7 **Portugal** Slovakia UFI: 0DG0-F0CK-D00A-7VE7 Slovenia UFI: 0DG0-F0CK-D00A-7VE7 **Spain** UFI: 0DG0-F0CK-D00A-7VE7 Sweden UFI: 0DG0-F0CK-D00A-7VE7 UFI: 0DG0-F0CK-D00A-7VE7 **Switzerland**

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

Material name: Devweld 531 Activator

SDS FU

Revision information Training information Disclaimer

None.

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Devweld 531 Activator
4451 Version #: 02 Revision date: 09-09-2023 Issue date: 07-24-2023