SAFETY DATA SHEET

Version #: 01

Issue date: 07-25-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Flexane 60L Resin

of the mixture

Registration number

Synonyms None SKU# X0021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name ITW Performance Polymers

Address Bay 150

Shannon Industrial Estate

Co. Clare, Ireland

Division

Telephone Phone 353(61)771500

e-mail customerservice.shannon@itwpp.com

Contact person Not available

1.4. Emergency telephone

number

Emergency Number

44(0)1235 239 670

General in EU

112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Center

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Belgium National Poisons

Control Center

070 245 245 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Bulgaria National

Toxicological Information

Center

+359 2 9154 233 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Croatia Poisons

Information Center

+385 1 2348 342 (Hours of operation not provided, SDS/Product information may

not be available for the Emergency Service.)

Cyprus Poison Center

1401 (Available 24 hours a day. SDS/Product information may not be available

for the Emergency Service.)

Czech Republic National Poisons Information

Center

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Center

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons

Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Material name: Flexane 60L Resin X0021 Version #: 01 Issue date: 07-25-2023 **Greece Poison Information** Centre

(0030) 2107793777 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Hungary National Emergency Phone Number +36-80-201-199 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

113

Iceland Poison Center (+354) 543 2222 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Latvia Emergency medical

+371 67042473 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.) Information Center

Lithuania Neatidėliotina informacija apsinuodijus

Latvia Poison and Drug

+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)

Norway Norwegian Poison Information Center

22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Portugal Poison Center

800 250 250 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Romania Biroul RSI si Informare Toxicologica 021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be

available for the Emergency Service.)

Slovakia National Toxicological Information Center

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Spain Toxicology **Information Service**

+ 34 91 562 04 20 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Sweden National Poison Information Center

112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.)

Switzerland Tox Info Suisse

145 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

H332 - Harmful if inhaled. Acute toxicity, inhalation Category 4 H315 - Causes skin irritation. Skin corrosion/irritation Category 2 H319 - Causes serious eye Serious eye damage/eye irritation Category 2 irritation.

Respiratory sensitization Category 1 H334 - May cause allergy or

asthma symptoms or breathing

difficulties if inhaled.

Skin sensitization Category 1 H317 - May cause an allergic skin

reaction.

Specific target organ toxicity - single

exposure

Category 3 respiratory tract irritation

H335 - May cause respiratory

irritation.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI:

Austria: DX50-S0EW-P00W-FAA4
Belgium: DX50-S0EW-P00W-FAA4
Bulgaria: DX50-S0EW-P00W-FAA4
Croatia: DX50-S0EW-P00W-FAA4
Cyprus: DX50-S0EW-P00W-FAA4

Czech Republic: DX50-S0EW-P00W-FAA4
Denmark: DX50-S0EW-P00W-FAA4
Estonia: DX50-S0EW-P00W-FAA4
EU: DX50-S0EW-P00W-FAA4
Finland: DX50-S0EW-P00W-FAA4
France: DX50-S0EW-P00W-FAA4
Germany: DX50-S0EW-P00W-FAA4

France: DX50-S0EW-P00W-FAA4
Germany: DX50-S0EW-P00W-FAA4
Greece: DX50-S0EW-P00W-FAA4
Hungary: DX50-S0EW-P00W-FAA4
Iceland: DX50-S0EW-P00W-FAA4
Ireland: DX50-S0EW-P00W-FAA4
Italy: DX50-S0EW-P00W-FAA4
Latvia: DX50-S0EW-P00W-FAA4
Lithuania: DX50-S0EW-P00W-FAA4

Luxembourg: DX50-S0EW-P00W-FAA4
Malta: DX50-S0EW-P00W-FAA4
Netherlands: DX50-S0EW-P00W-FAA4
Norway: DX50-S0EW-P00W-FAA4
Poland: DX50-S0EW-P00W-FAA4
Portugal: DX50-S0EW-P00W-FAA4
Romania: DX50-S0EW-P00W-FAA4
Slovakia: DX50-S0EW-P00W-FAA4
Slovenia: DX50-S0EW-P00W-FAA4

Spain: DX50-S0EW-P00W-FAA4 Sweden: DX50-S0EW-P00W-FAA4

Contains: 4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate, Stannous

Octoate

Hazard pictograms



Signal word Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

Precautionary statements

Prevention

P261 Avoid breathing mist/vapors.
P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/face protection.

P280 Wear protective gloves. P284 Wear respiratory protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label information

1,5% of the mixture consists of component(s) of unknown acute hazards to the aquatic

environment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation 2.3. Other hazards

(EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
4,4'-methylenedi(cyclohexyl	1-2%	5124-30-1	-	615-009-00-0	
isocyanate);		225-863-2			
dicyclohexylmethane-4,4'-di-isocyanat					
Δ					

Classification: Acute Tox. 4;H302;(ATE: 1065 mg/kg bw), Acute Tox. 3;H331;(ATE: 3

mg/l), Skin Irrit. 2;H315, Eye Irrit. 2;H319, Resp. Sens. 1;H334, Skin

Sens. 1;H317, STOT SE 3;H335

Specific Concentration Limits: Resp. Sens. 1;H334: C ≥ 0.5 %, Skin Sens. 1;H317: C ≥ 0.5 %

Stannous Octoate 0,10-0,99 301-10-0 % 206-108-6

Classification: -

Other components below reportable levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical **General information**

personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash

contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

> artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or

doctor/physician.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Avoid breathing mist/vapors. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001, as amended

Components	Туре	Value	Form
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	Ceiling	0,054 mg/m3	
		0,005 ppm	
	MAK	0,054 mg/m3	
		0,005 ppm	
Stannous Octoate (CAS 301-10-0)	MAK	0,1 mg/m3	Inhalable dust.
	STFI	0.2 mg/m3	Inhalable dust

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 -Chemical agents as amended

Components	Туре	Value	
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	TWA	0,055 mg/m3	

Material name: Flexane 60L Resin

Chemical agents, as amended Components	Туре	Value
		0,005 ppm
Stannous Octoate (CAS 01-10-0)	STEL	0,2 mg/m3
	TWA	0,1 mg/m3
amended	-	st risks of exposure to chemical agents at work, as
Components	Туре	Value
Stannous Octoate (CAS 301-10-0)	TWA	0,1 mg/m3
		t Exposure to Dangerous Chemicals at Work, OELs an
Biological Limit Values, Annex I (NN Components	Type	Value
Stannous Octoate (CAS	MAC	0,1 mg/m3
301-10-0)		
	STEL	0,2 mg/m3
		s at work (Decree on protection of health at work,
361/2007, Annex 2, Part A & Annex 3 Components	3, Part A, as amended) Type	Value
Stannous Octoate (CAS 301-10-0)	Ceiling	0,2 mg/m3
,	TWA	0,1 mg/m3
Denmark. Work Environment Autho Components	rity. Exposure Limits for Sub Type	stances & Materials, Annex 2 Value
4,4'-methylenedi(cyclohexyl socyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	TLV	0,054 mg/m3
0	T 1.) (0,005 ppm
Stannous Octoate (CAS 301-10-0)	TLV	0,1 mg/m3
,	ure Limits of Hazardous Sub Type	stances (Regulation No. 105/2001, Annex), as amended Value
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	STEL	0,01 ppm
	T\A/A	0,005 ppm
5.2. 00 1/	TWA	о,ооо рр
Stannous Octoate (CAS	STEL	0,2 mg/m3
Stannous Octoate (CAS		• •
Stannous Octoate (CAS 301-10-0) Finland. HTP-arvot, App 3., Binding	STEL TWA	0,2 mg/m3 0,1 mg/m3
Stannous Octoate (CAS 301-10-0) Finland. HTP-arvot, App 3., Binding Components 4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS	STEL TWA Limit Values, Social Affairs a	0,2 mg/m3 0,1 mg/m3 and Ministry of Health
Stannous Octoate (CAS 301-10-0) Finland. HTP-arvot, App 3., Binding Components 4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1) Stannous Octoate (CAS 301-10-0)	STEL TWA Limit Values, Social Affairs a Type	0,2 mg/m3 0,1 mg/m3 and Ministry of Health Value

Stannous Octoate (CAS		0.0
301-10-0)	VLE	0,2 mg/m3
Regulatory status: In	idicative limit (VL)	
B total and to the	VME	0,1 mg/m3
	idicative limit (VL)	
Greece. OELs, Presidential Components	Decree No. 307/1986, as amended Type	Value
I,4'-methylenedi(cyclohexyl socyanate); dicyclohexylmethane-4,4'-di isocyanate (CAS 5124-30-1)	STEL	0,11 mg/m3 0,01 ppm
	TWA	0,01 ррш 0,11 mg/m3
	IWA	0,01 ppm
Stannous Octoate (CAS	STEL	0,2 mg/m3
301-10-0)	OTEL	0,2 mg/m0
	TWA	0,1 mg/m3
Hungary. OELs. Decree on Components	protection of workers exposed to che Type	emical agents (5/2020. (II.6)), Annex 1&2, as amended Value
Stannous Octoate (CAS 301-10-0)	TWA	0,02 mg/m3
•	390/2009 on Pollution Limits and Mea	sures to Reduce Pollution at the Workplace, as amend Value
4,4'-methylenedi(cyclohexyl socyanate); dicyclohexylmethane-4,4'-di isocyanate (CAS 5124-30-1)	TWA	0,054 mg/m3
		0,005 ppm
Stannous Octoate (CAS 801-10-0)	STEL	0,05 mg/m3
		0,002 ppm
	TWA	0,1 mg/m3
		Agents and Carcinogens Regulations Value
	Туре	value
Components Stannous Octoate (CAS	STEL	0,2 mg/m3
Components Stannous Octoate (CAS	<u> </u>	
Components Stannous Octoate (CAS 801-10-0)	STEL	0,2 mg/m3
Components Stannous Octoate (CAS 801-10-0) taly. OELs (Legislative Dec	STEL	0,2 mg/m3
Components Stannous Octoate (CAS 801-10-0) taly. OELs (Legislative Dec Components 1,4'-methylenedi(cyclohexyl socyanate); dicyclohexylmethane-4,4'-di isocyanate (CAS	STEL TWA cree n.81, 9 April 2008), as amended	0,2 mg/m3 0,1 mg/m3
Components Stannous Octoate (CAS 801-10-0) taly. OELs (Legislative Dec Components I,4'-methylenedi(cyclohexyl socyanate); licyclohexylmethane-4,4'-di isocyanate (CAS 5124-30-1) Stannous Octoate (CAS	STEL TWA cree n.81, 9 April 2008), as amended Type	0,2 mg/m3 0,1 mg/m3 Value
Components Stannous Octoate (CAS 301-10-0) taly. OELs (Legislative Dec Components 4,4'-methylenedi(cyclohexyl socyanate); dicyclohexylmethane-4,4'-di isocyanate (CAS 5124-30-1) Stannous Octoate (CAS 301-10-0) Lithuania. OELs. Occupatio	STEL TWA cree n.81, 9 April 2008), as amended Type TWA STEL STEL	0,2 mg/m3 0,1 mg/m3 Value 0,005 ppm
Components Stannous Octoate (CAS 801-10-0) taly. OELs (Legislative Dec Components I,4'-methylenedi(cyclohexyl socyanate); licyclohexylmethane-4,4'-di isocyanate (CAS 124-30-1) Stannous Octoate (CAS 801-10-0) Lithuania. OELs. Occupatio I-824/A1-389), as amended	STEL TWA cree n.81, 9 April 2008), as amended Type TWA STEL STEL	0,2 mg/m3 0,1 mg/m3 Value 0,005 ppm 0,2 mg/m3
Components Stannous Octoate (CAS 301-10-0) taly. OELs (Legislative Dec Components 4,4'-methylenedi(cyclohexyl socyanate); dicyclohexylmethane-4,4'-di isocyanate (CAS 5124-30-1) Stannous Octoate (CAS 301-10-0)	STEL TWA cree n.81, 9 April 2008), as amended Type TWA STEL onal Exposure Limit Values for Chemi	0,2 mg/m3 0,1 mg/m3 Value 0,005 ppm 0,2 mg/m3 ical Substances (Hygiene Norm HN 23:2011; Order No.

Material name: Flexane 60L Resin

V-824/A1-389), as amended Components	Туре	Value
Stannous Octoate (CAS 301-10-0)	STEL	0,2 mg/m3
,	TWA	0,1 mg/m3
Infection Groups for Biological Fa		Physical and Chemical Factors in Work Environment and
Components	Туре	Value
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	STEL	0,01 ppm
	TLV	0,05 mg/m3
		0,005 ppm
Stannous Octoate (CAS 301-10-0)	TLV	0,1 mg/m3
Portugal. VLEs. Norm on occupati Components	onal exposure to chemical ag Type	ents (NP 1796-2014) Value
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	TWA	0,005 ppm
Stannous Octoate (CAS 301-10-0)	STEL	0,2 mg/m3
,	TWA	0,1 mg/m3
	hemical Agents at Workplace	(Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as
amended) Components	Туре	Value
Stannous Octoate (CAS	STEL	0,15 mg/m3
301-10-0)	TWA	0,05 mg/m3
Slovakia. OELs. Maximum permis	sible exposure limits for chem	nical factors in workplace air (Regulation No 355/2006,
Annex 1, Table 1, as amended)	Tuno	Value
Components Stanzage Optopte (CAS	Туре	Value
Stannous Octoate (CAS 301-10-0)	STEL	0,2 mg/m3
	TWA	0,1 mg/m3
· · · · · · · · · · · · · · · · · ·	cposición Profesional Para Ag	gentes Químicos, Table 1-Valores Límites Ambientales
(VLAs) Components	Туре	Value
4,4'-methylenedi(cyclohexyl socyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	TWA	0,055 mg/m3
0121 00 1)		0,005 ppm
Stannous Octoate (CAS	STEL	0,2 mg/m3
301-10-0)	TWA	0,1 mg/m3
Sweden. OELs (Annex 1). Work Er	nvironment Authority (AV), Oc	cupational Exposure Limit Values (AFS 2018:1), as
amended		
Components	Туре	Value Form
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	Ceiling	0,005 ppm

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Components	Туре	Value	Form
	TWA	0,002 ppm	
Stannous Octoate (CAS 301-10-0)	STEL	0,2 mg/m3	Total dust.
	TWA	0,1 mg/m3	Total dust.
Switzerland. SUVA Grenzwerte am	Arbeitsplatz: Aktuelle MAK-V	Verte	
Components	Туре	Value	Form
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	STEL	0,02 mg/m3	
	TWA	0,02 mg/m3	
Stannous Octoate (CAS 301-10-0)	STEL	0,2 mg/m3	Inhalable fraction.
	TWA	0,1 mg/m3	Inhalable fraction.
UK. OELs. Workplace Exposure Li	mits (WELs) (EH40/2005 (Fou	rth Edition 2020)), Table 1	
Components	Туре	Value	
4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di -isocyanate (CAS 5124-30-1)	STEL	0,07 mg/m3	
,	TWA	0,02 mg/m3	
Stannous Octoate (CAS 301-10-0)	STEL	0,2 mg/m3	
	TWA	0,1 mg/m3	

Biological limit values

Components V	/alue	Determinant	Specimen	Sampling Time
4,4'-methylenedi(cyclohexyl 1 isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)	l umol/mol	Isocyanate-deri ved diamine	Creatinine in urine	*

For sampling details, please see the source document.

Recommended monitoring

Follow standard monitoring procedures.

procedures

Derived no effect levels

(DNELs)

Not available.

Predicted no effect Not available. concentrations (PNECs)

Exposure guidelines

Austria MAK: Skin designation Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin. Belgium OELs: Skin designation Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin. Czech Republic PELs: Skin designation Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin. **Denmark GV: Skin designation** Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin. Estonia OELs: Skin designation Can be absorbed through the skin. Stannous Octoate (CAS 301-10-0) Finland Exposure Limit Values: Skin designation Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin. **Greece OEL: Skin designation** Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Material name: Flexane 60L Resin

SDS EU

Hungary OELs: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Iceland OELs: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Italy OELs: Skin designation

Stannous Octoate (CAS 301-10-0) Danger of cutaneous absorption

Lithuania OELs: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Norway Exposure Limit Values: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Portugal VLEs Norm on Occupatioinal Exposure: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Slovakia OELs: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Spain OELs: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Sweden Threshold Limit Values: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

Switzerland SUVA Limit Values at the Workplace: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

UK EH40 WEL: Skin designation

Stannous Octoate (CAS 301-10-0) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. - Other

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material Hygiene measures

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or

engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid. Form Liquid. Color Clear. Slight. Odor

Melting point/freezing point **Boiling point or initial boiling**

Not available. Not available.

point and boiling range

Flammability Not applicable. Flash point Not available. Not available. Auto-ignition temperature **Decomposition temperature** Not available.

Material name: Flexane 60L Resin

рΗ Not available. Not available. Kinematic viscosity

Solubility

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water) (log value)

Not available. Vapor pressure

Density and/or relative density

1,04 g/cm³ Density Not available Vapor density Not available. Particle characteristics

9.2. Other information

9.2.1. Information with regard No relevant additional information available. to physical hazard classes

9.2.2. Other safety characteristics 1,04 Specific gravity

SECTION 10: Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. 10.1. Reactivity

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Contact with incompatible materials.

10.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred **Symptoms**

vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness

and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Harmful if inhaled. Acute toxicity

Species Components **Test Results**

4,4'-methylenedi(cyclohexyl isocyanate); dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1)

Acute **Dermal**

LD50 Rabbit > 10000 mg/kg

Oral

LD50 Rat 1065 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Carcinogenicity

Not applicable. Reproductive toxicity

Material name: Flexane 60L Resin

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

11.2. Information on other hazards

Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than

0.1% by weight.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

No data available. 12.3. Bioaccumulative potential **Partition coefficient**

n-octanol/water (log Kow)

Not available.

Not available. **Bioconcentration factor (BCF)** 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

12.7. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

12.8. Additional information

Estonia Dangerous substances in soil Data

Stannous Octoate (CAS 301-10-0)

Tin (Sn) 10 MG/KG Tin (Sn) 300 MG/KG Tin (Sn) 50 MG/KG

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of Disposal methods/information

contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number Not regulated as dangerous goods. 14.2. UN proper shipping

name

Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk

Hazard No. (ADR) Not assigned. Not assigned.

Tunnel restriction code 14.4. Packing group

14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

RID

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -14.4. Packing group -14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

ADN

14.1. UN number Not regulated as dangerous goods.14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -14.4. Packing group -14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IATA

14.1. UN numberNot regulated as dangerous goods. **14.2. UN proper shipping**Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk -14.4. Packing group -14.5. Environmental hazards No.

14.6. Special precautions Not assigned.

for user

IMDG

14.1. UN number Not regulated as dangerous goods.14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary risk 14.4. Packing group 14.5. Environmental hazards

Marine pollutant No.

EmS Not assigned. 14.6. Special precautions Not assigned.

for user

14.7. Maritime transport in bulk Not established.

according to IMO instruments

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Stannous Octoate (CAS 301-10-0)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed

UFI:

Austria: DX50-S0EW-P00W-FAA4 Belgium: DX50-S0EW-P00W-FAA4 Bulgaria: DX50-S0EW-P00W-FAA4 Croatia: DX50-S0EW-P00W-FAA4 Cyprus: DX50-S0EW-P00W-FAA4 Czech Republic: DX50-S0EW-P00W-FAA4 Denmark: DX50-S0EW-P00W-FAA4 Estonia: DX50-S0EW-P00W-FAA4 EU: DX50-S0EW-P00W-FAA4 Finland: DX50-S0EW-P00W-FAA4 France: DX50-S0EW-P00W-FAA4 Germany: DX50-S0EW-P00W-FAA4 Greece: DX50-S0EW-P00W-FAA4 Hungary: DX50-S0EW-P00W-FAA4 Iceland: DX50-S0EW-P00W-FAA4 Ireland: DX50-S0EW-P00W-FAA4 Italy: DX50-S0EW-P00W-FAA4 Latvia: DX50-S0EW-P00W-FAA4

Lithuania: DX50-S0EW-P00W-FAA4
Luxembourg: DX50-S0EW-P00W-FAA4
Malta: DX50-S0EW-P00W-FAA4
Netherlands: DX50-S0EW-P00W-FAA4
Norway: DX50-S0EW-P00W-FAA4
Poland: DX50-S0EW-P00W-FAA4
Portugal: DX50-S0EW-P00W-FAA4
Romania: DX50-S0EW-P00W-FAA4
Slovakia: DX50-S0EW-P00W-FAA4
Slovakia: DX50-S0EW-P00W-FAA4

Spain: DX50-S0EW-P00W-FAA4 Sweden: DX50-S0EW-P00W-FAA4

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Young people under 18 years old are not allowed to work with this product according to EU

Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

France regulations

France INRS Table of Occupational Diseases

4,4'-methylenedi(cyclohexyl isocyanate); Affections professionnelles provoquées par les isocyanates dicyclohexylmethane-4,4'-di-isocyanate (CAS 5124-30-1) organiques 62

Product registration number

 Austria
 UFI: DX50-S0EW-P00W-FAA4

 Belgium
 UFI: DX50-S0EW-P00W-FAA4

 Czech Republic
 UFI: DX50-S0EW-P00W-FAA4

 Denmark
 UFI: DX50-S0EW-P00W-FAA4

 European Union
 UFI: DX50-S0EW-P00W-FAA4

 Finland
 UFI: DX50-S0EW-P00W-FAA4

 France
 UFI: DX50-S0EW-P00W-FAA4

UFI: DX50-S0EW-P00W-FAA4 Germany UFI: DX50-S0EW-P00W-FAA4 Greece UFI: DX50-S0EW-P00W-FAA4 Hungary UFI: DX50-S0EW-P00W-FAA4 Italy UFI: DX50-S0EW-P00W-FAA4 **Netherlands** Norway UFI: DX50-S0EW-P00W-FAA4 **Poland** UFI: DX50-S0EW-P00W-FAA4 **Portugal** UFI: DX50-S0EW-P00W-FAA4 Slovakia UFI: DX50-S0EW-P00W-FAA4 UFI: DX50-S0EW-P00W-FAA4 Slovenia UFI: DX50-S0EW-P00W-FAA4 Spain Sweden UFI: DX50-S0EW-P00W-FAA4 **Switzerland** UFI: DX50-S0EW-P00W-FAA4

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

Full text of any statements. which are not written out in full under sections 2 to 15

Not available

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

Revision information

Training information

Disclaimer

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.