



ITW Performance Polymers  
30 Endicott Street  
Danvers, MA 01923  
(855) 489-7262

## Technical Data Sheet

### Permatex® Nickel Anti-Seize

AAM Revised 10/17

#### PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex® Nickel Anti-Seize Lubricant is a high temperature, high quality, heavy duty lubricant that resists galling and corrosion and reduces wear in heavy pressure applications. It contains tenacious metals, oils and graphite materials that cannot be burned away or removed by slow moving parts. This product withstands temperatures ranging from -65°F to 2400°F (-54°C to 1316°C). It is recommended for use where copper contamination must be avoided, under conditions of extreme pressure and temperature and with stainless steel, titanium and nickel alloys. OEM recommended.

#### PRODUCT BENEFITS

Permatex® Nickel Anti-Seize was designed specifically for use on stainless steel or similar alloys. It protects threaded fasteners and fittings from heat, freezing, seizure or galling at temperatures from -65°F to 2400°F. It may be used on pumps, sensors, valves, nuts and bolts where extreme conditions of heat exist.

#### TYPICAL APPLICATIONS

- Exhaust manifold bolts
- Exhaust system bolts
- Muffler clamps
- Tailpipe assemblies
- Catalytic converter assemblies

#### DIRECTIONS FOR USE

1. Clean mating surfaces before application.
2. For best results, apply to clean, dry surfaces.
3. Clean surfaces with Permatex® Brake & Parts Cleaner.
4. Wire brush any loose surface rust.
5. Apply Nickel Anti-Seize to the parts that require protection.
6. Reassemble parts using normal torque values.
7. Wipe off excess material.

#### For Cleanup

1. Clean parts with disposable towel.
2. Clean hands with Permatex® brand hand cleaners.

#### PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Mineral oil, nickel, graphite
Appearance	Gray paste
Odor	Petroleum
Specific Gravity	1.1
Temperature Range, °C (°F)	-54(-65) to 1316(2400)
Viscosity, cPs	200,000 (base)
Flash Point, °C(°F)	93(200)
NFPA 704 Flammability Rating	1

#### GENERAL INFORMATION

**WARNING: Not for use on wheel lug nut or stud applications.**

**This product is not recommended for use in pure oxygen and/or oxygen rich systems.**

**For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).**

#### ORDERING INFORMATION

Part Number	Container Size
77124	8 oz. brush-top bottle
77164	16 oz. brush-top bottle

#### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8°C and 28°C (46°F and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

#### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.  
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.  
PLEASE CONTACT ITW PERFORMANCE POLYMERS TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
ITW PERFORMANCE POLYMERS 30 ENDICOTT STREET, DANVERS, MA 01923 PHONE (855) 489-7262