

ITW Performance Polymers

SAFETY DATA SHEET IRABOND UU55-52A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name IRABOND UU55-52A

Product number ADH UU55

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Primer.

1.3. Details of the supplier of the safety data sheet

Supplier ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
customerservice.shannon@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315

Environmental hazards Not Classified

Human health

Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Persons susceptible to allergic reactions should not handle this product. Persons with impaired lung function should not handle this product.. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure.

2.2. Label elements

Pictogram



Signal word

Warning

IRABOND UU55-52A

Hazard statements	H315 Causes skin irritation. H332 Harmful if inhaled. EUH208 Contains TOLUENE-DIISOCYANATE. May produce an allergic reaction.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P284 [In case of inadequate ventilation] wear respiratory protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
Contains	XYLENE, MIXTURES OF ISOMERES, TOLUENE-DIISOCYANATE
Supplementary precautionary statements	P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTRE/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

XYLENE, MIXTURES OF ISOMERES	30-60%
CAS number: 1330-20-7	EC number: 215-535-7
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	
2-METHOXY-1-METHYLETHYL ACETATE	30-60%
CAS number: 108-65-6	EC number: 203-603-9
Classification Flam. Liq. 3 - H226	

IRABOND UU55-52A

TOLUENE-DIISOCYANATE	<1%
CAS number: 26471-62-5	EC number: 247-722-4
Classification Acute Tox. 2 - H330 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Do not breathe vapour. Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	DO NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder. Larger fires: Water spray, fog or mist.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable. Avoid breathing fire gases or vapours. Thermal decomposition or combustion products may include the following substances: Very toxic or corrosive gases or vapours.
-------------------------	--

5.3. Advice for firefighters

Protective actions during firefighting	Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses. Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.
---	--

IRABOND UU55-52A

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Flammable. Warn everybody of potential hazards and evacuate if necessary. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Transfer to a dry metal container, keeping it open for 48 hours. Absorb spillage with non-combustible, absorbent material. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Use only in well-ventilated areas. Keep away from heat, sparks and open flame. Provide adequate ventilation. Static electricity and formation of sparks must be prevented. Open drum carefully as content may be under pressure. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with water. Store away from incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE, MIXTURES OF ISOMERES

Long-term exposure limit (8-hour TWA): EU 50 ppm 221 mg/m³

Short-term exposure limit (15-minute): EU 100 ppm 442 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

TOLUENE-DIISOCYANATE

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³(Sen)

Short-term exposure limit (15-minute): WEL 0.07 mg/m³(Sen)

IRABOND UU55-52A

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: It is recommended that gloves are made of the following material: Nitrile rubber. It is recommended that gloves are made of the following material: Butyl rubber. It is recommended that gloves are made of the following material: Polyvinyl chloride (PVC). To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

Other skin and body protection

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of skin contact. Wear chemical protective suit.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear liquid.
Odour	Xylene.
Initial boiling point and range	87°C @
Flash point	24°C
Relative density	1.0 @ 20 °C°C
Solubility(ies)	Immiscible with water.
Viscosity	<0.5 poise @ 25°C

9.2. Other information

Other information Not available.

IRABOND UU55-52A

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Acids. Amines. Reacts strongly with water.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not available.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight. Avoid freezing.

10.5. Incompatible materials

Materials to avoid Alkalis - inorganic. Alkalis - organic. Ammonia. Amines. Water. Acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Irritating gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 3,142.86

Acute toxicity - inhalation

ATE inhalation (gases ppm) 7,258.06

ATE inhalation (vapours mg/l) 22.82

ATE inhalation (dusts/mists mg/l) 2.83

General information

Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Persons susceptible to allergic reactions should not handle this product. Persons with impaired lung function should not handle this product. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure. Pregnant or breastfeeding women should not work with this product if there is any risk of exposure.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system. May cause sensitisation by inhalation. A single exposure may cause the following adverse effects: Severe lung irritation. Recognised allergen. Repeated exposure may cause chronic upper respiratory irritation. Asthma, pulmonary sensitisation.

Ingestion

Swallowing concentrated chemical may cause severe internal injury.

Skin contact

Irritating to skin.

Eye contact

May cause severe eye irritation. May cause temporary blindness and severe eye damage.

Acute and chronic health hazards

This chemical can be hazardous when inhaled and/or touched.

IRABOND UU55-52A

Route of exposure	Inhalation Ingestion. Skin and/or eye contact
Target organs	Respiratory system, lungs
Medical symptoms	EYES AND MUCOUS MEMBRANES. Irritation, burning, lachrymation, blurred vision after liquid splash. RESPIRATORY SYSTEM. Severe lung irritation. General respiratory distress, unproductive cough. SKIN. Severe skin irritation. DIGESTIVE SYSTEM. Nausea, vomiting. Severe stomach pain.
Medical considerations	Skin disorders and allergies. Chronic respiratory and obstructive airway diseases.

SECTION 12: Ecological Information

Ecotoxicity Avoid release to the environment. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

General No other information known.

14.1. UN number

UN No. (ADR/RID) 1866

UN No. (IMDG) 1866

UN No. (ICAO) 1866

14.2. UN proper shipping name

IRABOND UU55-52A

Proper shipping name (ADR/RID) RESIN SOLUTION

Proper shipping name (IMDG) RESIN SOLUTION

Proper shipping name (ICAO) RESIN SOLUTION

Proper shipping name (ADN) RESIN SOLUTION

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID label 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

IRABOND UU55-52A

Revision comments	Revised formulation.
Revision date	02/11/2018
Revision	21
Supersedes date	04/04/2018
Hazard statements in full	H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H330 Fatal if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains TOLUENE-DIISOCYANATE. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.