



## TECHNICAL DATA SHEET - IRATHANE TX55

Revised: 05/2018

### PRODUCT DESCRIPTION

A single component roller, brush or spray applied intercoat adhesive developed for use with Irabond 9924 primer and Irathane and Aqualine system coats. UU55 is often recommended when repairing other polyurethane systems.

### RECOMMENDED APPLICATIONS

Specifically designed for use with Irathane 155HS to enable an increased build to be achieved.

### FEATURES

Increases viscosity of Irathane 155HS for increased build capability.

### PACKAGE SIZE

125ml

### PRODUCT DATA

TYPICAL PHYSICAL PROPERTIES	
COLOUR	Opaque
FLASH POINT (°C)	>149
% SOLIDS BY VOLUME	100
USAGE (ML/10L KIT OF 155HS)	4-10

**APPLICATION INFORMATION**

**APPLICATION**

Irathane TX55 is added to Irathane 155HS typically at a level of 4 to 10ml per 10L kit. The addition is made to the already mixed 155HS, it is possible to make further additions to adjust build after testing. Refer to Irathane 155HS application Method Statement for further guidance.

**SHELF LIFE & STORAGE**

A shelf life of 12 months from date of shipment can be expected when stored in dry conditions at room temperature (~22°C) in their original containers.

**PRECAUTIONS**

For complete safety and handling information, please refer to Material Safety Data Sheets prior to using this product.

**WARRANTY**

ITW Performance Polymers will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control we can accept no liability for the results obtained.

**DISCLAIMER**

All information on this data sheet is based on laboratory testing and is not intended for design purposes. ITW Performance Polymers makes no representations or warranties of any kind concerning this data.

For further product information or technical assistance please call +353 61 771 500.