

SAFETY DATA SHEET

1. Identification

Product identifier SPRAYCORE® SC-2000 OS LS

Other means of identification

SKU# 103998

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd
Unit 1
Halton Hills, ON L7G 0C6

Contact person Customer Service

Telephone number 978-777-1100

Fax

E-mail

Emergency telephone number 800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1
	Reproductive toxicity	Category 1
Environmental hazards	Specific target organ toxicity following repeated exposure	Category 1
	Not classified.	

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe mist/vapours. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Polyester resin		N/A	30 - 60
Styrene		100-42-5	15 - 40
VINYL TOLUENE		25013-15-4	5 - 10
QUATERNARY AMMONIUM COMPOUNDS, BENZYL(HYDROGENATED TALLOW ALKYL)DIMETHYL, CHLORIDES, COMPDS. WITH BENTONITE AND BIS(HYDROGENATED TALLOW ALKYL)DIMETHYLAMMONIUM CHLORIDES		71011-25-1	1 - 5
Limestone		1317-65-3	0.5 - 1.5
METHYL ALCOHOL		67-56-1	0.1 - 1
SILICA, CRYSTALLINE, QUARTZ		14808-60-7	0.1 - 1
Other components below reportable levels			15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapour.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapours. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
METHYL ALCOHOL (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
	STYRENE (CAS 100-42-5)	STEL	40 ppm
VINYL TOLUENE (CAS 25013-15-4)	TWA	20 ppm	
	STEL	100 ppm	
	TWA	50 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	10 mg/m ³	
	METHYL ALCOHOL (CAS 67-56-1)	STEL	328 mg/m ³
VINYL TOLUENE (CAS 25013-15-4)	TWA	250 ppm	
	TWA	262 mg/m ³	
	TWA	200 ppm	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable particles.
	STYRENE (CAS 100-42-5)	STEL	170 mg/m ³
VINYL TOLUENE (CAS 25013-15-4)	TWA	40 ppm	
	TWA	85 mg/m ³	
	TWA	20 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
VINYL TOLUENE (CAS 25013-15-4)	STEL	483 mg/m3	
		100 ppm	
	TWA	242 mg/m3	
		50 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	STEL	20 mg/m3	Total dust.
	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
METHYL ALCOHOL (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
STYRENE (CAS 100-42-5)	STEL	75 ppm	
	TWA	50 ppm	
VINYL TOLUENE (CAS 25013-15-4)	STEL	75 ppm	
	TWA	25 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
METHYL ALCOHOL (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
STYRENE (CAS 100-42-5)	STEL	40 ppm	
	TWA	20 ppm	
VINYL TOLUENE (CAS 25013-15-4)	STEL	100 ppm	
	TWA	50 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
METHYL ALCOHOL (CAS 67-56-1)	STEL	250 ppm	
	TWA	200 ppm	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
STYRENE (CAS 100-42-5)	STEL	100 ppm	
	TWA	35 ppm	
VINYL TOLUENE (CAS 25013-15-4)	STEL	100 ppm	
	TWA	50 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	10 mg/m3	Total dust.
METHYL ALCOHOL (CAS 67-56-1)	STEL	328 mg/m3	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
		250 ppm	
	TWA	262 mg/m3	
		200 ppm	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
STYRENE (CAS 100-42-5)	STEL	426 mg/m3	
		100 ppm	
	TWA	213 mg/m3	
		50 ppm	
VINYL TOLUENE (CAS 25013-15-4)	STEL	483 mg/m3	
		100 ppm	
	TWA	242 mg/m3	
		50 ppm	

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
METHYL ALCOHOL (CAS 67-56-1)	15 minute	250 ppm	
	8 hour	200 ppm	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	8 hour	0.05 mg/m3	Respirable fraction.
STYRENE (CAS 100-42-5)	15 minute	40 ppm	
	8 hour	20 ppm	
VINYL TOLUENE (CAS 25013-15-4)	15 minute	100 ppm	
	8 hour	50 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
METHYL ALCOHOL (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
STYRENE (CAS 100-42-5)	40 µg/l	Styrene	Urine	*
	400 mg/g	Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

METHYL ALCOHOL (CAS 67-56-1) Can be absorbed through the skin.

Styrene (CAS 100-42-5) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

METHYL ALCOHOL (CAS 67-56-1)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

METHYL ALCOHOL (CAS 67-56-1)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Liquid.

Physical state

Liquid.

Form

Liquid.

Colour

Grey

Odour

Aromatic

Odour threshold

Not available.

pH

Not available.

Melting point/freezing point

-77 °C (-106.6 °F) estimated

Initial boiling point and boiling range

145 °C (293 °F) estimated

Flash point

32.0 °C (89.6 °F) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)**

1.1 % estimated

Flammability limit - upper (%)

6.1 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapour pressure

7.28 hPa estimated

Vapour density

Not available.

Relative density

Not available.

Solubility(ies)**Solubility (water)**

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

490 °C (914 °F) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Density	1.10 g/cm ³ estimated
Explosive properties	Not explosive.
Flammability class	Flammable IC estimated
Oxidising properties	Not oxidising.
Specific gravity	1.1 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidising agents. Aluminium. Peroxides.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics	Headache. Dizziness. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
---	--

Information on toxicological effects

Acute toxicity	Harmful if swallowed.
-----------------------	-----------------------

Components	Species	Test Results
METHYL ALCOHOL (CAS 67-56-1)		
Acute		
Dermal		
LD50	Rabbit	15800 mg/kg
Inhalation		
LC50	Rat	87.5 mg/l, 6 Hours
Styrene (CAS 100-42-5)		
Acute		
Oral		
LD50	Rat	1 g/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitisation		
Canada - Alberta OELs: Irritant		
Limestone (CAS 1317-65-3)	Irritant	
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible.	
Skin sensitisation	May cause an allergic skin reaction.	
Germ cell mutagenicity	May cause genetic defects.	
Carcinogenicity	May cause cancer.	
ACGIH Carcinogens		
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	A2 Suspected human carcinogen.	
Styrene (CAS 100-42-5)	A4 Not classifiable as a human carcinogen.	

VINYL TOLUENE (CAS 25013-15-4)	A4 Not classifiable as a human carcinogen.
Canada - Alberta OELs: Carcinogen category	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	Suspected human carcinogen.
Canada - Manitoba OELs: carcinogenicity	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	Suspected human carcinogen.
Styrene (CAS 100-42-5)	Not classifiable as a human carcinogen.
VINYL TOLUENE (CAS 25013-15-4)	Not classifiable as a human carcinogen.
Canada - Quebec OELs: Carcinogen category	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	Suspected carcinogenic effect in humans.
Styrene (CAS 100-42-5)	Detected carcinogenic effect in animals.
IARC Monographs. Overall Evaluation of Carcinogenicity	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
Styrene (CAS 100-42-5)	2A Probably carcinogenic to humans.
VINYL TOLUENE (CAS 25013-15-4)	3 Not classifiable as to carcinogenicity to humans.
US. National Toxicology Program (NTP) Report on Carcinogens	
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.
Styrene (CAS 100-42-5)	Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Chronic effects	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	
Partition coefficient n-octanol / water (log Kow)	
METHYL ALCOHOL	-0.77
Styrene	2.95
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

UN number	UN1866
UN proper shipping name	RESIN SOLUTION, flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II

Environmental hazards Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1866
UN proper shipping name Resin solution flammable
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1866
UN proper shipping name RESIN SOLUTION flammable
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Ontario. Toxic Substances. Toxic Reduction Act, 2009. Regulation 455/09 (July 1, 2011)

METHYL ALCOHOL (CAS 67-56-1)

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 06-July-2019

Revision date 29-April-2020

Version No. 03

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.