SAFETY DATA SHEET

1. Identification		
Product identifier	PLEXUS® MA590 Activator	
Other means of identification		
SKU#	IT178	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	Distributor information	
Company name	ITW Performance Polymers	
Address	35 Brownridge Rd	
	Unit 1	
	Halton Hills, ON L7G 0C6	
Contact person	Customer Service	
Telephone number	978-777-1100	
Fax		
E-mail		
Emergency telephone number	800-424-9300	
Supplier	Not available.	
2. Hazard identification		
Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Sensitization, skin	Category 1A
	Specific target organ toxicity following single exposure	Category 3 respiratory tract irritation
Environmental hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Highly flammable liquid and vapour. Causes s Causes eye irritation. Harmful if inhaled. May	skin irritation. May cause an allergic skin reaction. cause respiratory irritation.
Precautionary statement		
Prevention	Keep container tightly closed. Ground and bo explosion-proof electrical/ventilating/lighting e prevent static discharges. Wash thoroughly a	quipment. Use non-sparking tools. Take action to fee handling. Use only outdoors or in a ing should not be allowed out of the workplace.

Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methyl methacrylate		80-62-6	40 - 70
Benzyl 3-isobutyryloxy-1-isopropyl-2,2-dim ethylpropyl Phthalate		16883-83-3	5 - 10
PYRIDINE, 3,5-DIETHYL-1,2-DIHYDRO-1-PHE NYL-2-P ROPYL-		34562-31-7	1 - 5
Other components below reportable le	evels		15 - 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can d so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapour.
6. Accidental release mea	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate al ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhau ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handlin operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage,	 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code". Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge
including any incompatibilities	build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoi spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).
8. Exposure controls/pers	sonal protection

US. ACGIH Threshold Limit Values			
Components	Туре	Value	
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	

Components	cupational Health & Safety Code, Sche Type	dule 1, Table 2) Value
METHYL METHACRYLATE (CAS 80-62-6)	STEL	410 mg/m3
		100 ppm
	TWA	205 mg/m3
		50 ppm
Canada. British Columbia (Safety Regulation 296/97, a		for Chemical Substances, Occupational Health and
Components	Туре	Value
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm
Canada. Manitoba OELs (R Components	eg. 217/2006, The Workplace Safety A Type	nd Health Act) Value
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm
Canada. Ontario OELs. (Co Components	ntrol of Exposure to Biological or Che Type	emical Agents) Value
METHYL METHACRYLATE (CAS 80-62-6)	STEL	100 ppm
	TWA	50 ppm
Canada. Quebec OELs. (Mi Components	nistry of Labor - Regulation respecting Type	g occupational health and safety) Value
METHYL METHACRYLATE (CAS 80-62-6)	TWA	205 mg/m3
(040 00-02-0)		50 ppm
Canada. Saskatchewan OE Components	Ls (Occupational Health and Safety R Type	egulations, 1996, Table 21) Value
METHYL METHACRYLATE (CAS 80-62-6)	15 minute	100 ppm
	8 hour	50 ppm
logical limit values	No biological exposure limits noted fo	r the ingredient(s).
propriate engineering trols	Ventilation rates should be matched to exhaust ventilation, or other engineer	aust ventilation. Good general ventilation should be used. o conditions. If applicable, use process enclosures, local ng controls to maintain airborne levels below recommender e not been established, maintain airborne levels to an ation and safety shower.
vidual protection measures Eye/face protection	, such as personal protective equipme Chemical respirator with organic vapo	
Skin protection Hand protection	Wear appropriate chemical resistant g	gloves.
Other	Wear appropriate chemical resistant of	slothing.
Respiratory protection	Chemical respirator with organic vapo	-
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.
neral hygiene siderations	after handling the material and before	serve good personal hygiene measures, such as washing eating, drinking, and/or smoking. Routinely wash work emove contaminants. Contaminated work clothing should i

9. Physical and chemical properties

Paste.

Physical state	Liquid.
Form	Paste.
Colour	Not available.
Odour	Fragrant
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	-48 °C (-54.4 °F) estimated
nitial boiling point and boiling range	100.5 °C (212.9 °F) estimated
Flash point	10.0 °C (50.0 °F) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.7 %
Flammability limit - upper (%)	12.5 %
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
/apour pressure	28 mm Hg @ 20 °C
/apour density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
/iscosity	Not available.
Other information	
Density	0.94 g/cm3 estimated
Explosive properties	Not explosive.
Flammability class	Flammable IB estimated
Oxidising properties	Not oxidising.
Specific gravity	0.94 estimated
10. Stability and reactivity	1
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidising agents. Nitrates. Peroxides.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure	
Inhalation	Harmful if inhaled.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes eye irritation.

Ingestion	Knowledge about health haza	ard is incomplete	
Symptoms related to the	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. May		
physical, chemical and	cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic		
toxicological characteristics	skin reaction. Dermatitis. Rash.		
Information on toxicological eff			
Acute toxicity	Harmful if inhaled.		
Components	Species	Test Results	
Methyl methacrylate (CAS 80-62-	6)		
Acute			
Inhalation LC50	Mouse	18.5 mg/l 2 Hours	
	Mouse	18.5 mg/l, 2 Hours	
Oral LD50	Rat	7800 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Skin corrosion/innation Serious eye damage/eye	Causes eye irritation.		
irritation	Oddses eye initation.		
Respiratory or skin sensitisatio	n		
ACGIH sensitisation			
Methyl methacrylate (CA Canada - British Columbia	S 80-62-6) OELs: Respiratory or skin ser	Dermal sensitization sitiser	
Methyl methacrylate (CA	S 80-62-6)	Capable of causing respiratory, dermal or conjunctival sensitization.	
	azard: Dermal sensitization		
Methyl methacrylate (CA Canada - Quebec OELs: Se		Dermal sensitization	
Methyl methacrylate (CA Canada - Saskatchewan OB	S 80-62-6) ELs Hazard Data: Sensitiser	Sensitiser.	
Methyl methacrylate (CA	S 80-62-6)	Sensitiser.	
Respiratory sensitisation		k of data the classification is not possible.	
Skin sensitisation	May cause an allergic skin re		
Germ cell mutagenicity		k of data the classification is not possible.	
Carcinogenicity	Due to partial or complete lac	k of data the classification is not possible.	
ACGIH Carcinogens	0 00 00 0)		
Methyl methacrylate (CA Canada - Manitoba OELs: c	arcinogenicity	A4 Not classifiable as a human carcinogen.	
	Evaluation of Carcinogenicity	Not classifiable as a human carcinogen.	
Methyl methacrylate (CA	,	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity		k of data the classification is not possible.	
Specific target organ toxicity - single exposure	May cause respiratory irritation		
Specific target organ toxicity - repeated exposure	Due to partial or complete lac	k of data the classification is not possible.	
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.		
Chronic effects	Prolonged inhalation may be	harmful.	
12. Ecological informatio			
Ecotoxicity	possibility that large or freque	as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the de	egradability of any ingredients in the mixture.	
Bioaccumulative potential			
Partition coefficient n-octai Methyl methacrylate	nol / water (log Kow)	1.38	
	NI I.I. 11.I.I.		

Mobility in soil

No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

_	
Т	DG

TDG	
UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
ΙΑΤΑ	
UN number	UN1133
UN proper shipping name	Adhesives containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	
Environmental hazards	No.
ERG Code	3L
· ·	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and	Not established.
the IBC Code	

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated. Export Control List (CEPA 1999, Schedule 3) Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable. Kyoto Protocol

Not applicable. Montreal Protocol

Not applicable. Basel Convention

Not applicable.

NUT applicable

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Version No.	03
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Revision information	Composition / Information on Ingredients: Component Summary