PERFORMANCE POLYMERS.

SAFETY DATA SHEET

1. Identification

Product identifier CWC 604 Machine Bond Aggregate

Other means of identification

SKU# GP113A

Recommended use Not available.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

Category 1

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 130 Commerce Drive

Montgomeryville, PA 18936

United States

Telephone Customer Service 215-855-8450

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number CHEMTREC 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure. Harmful

to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: CWC 604 Machine Bond Aggregate
GP113A Version #: 03 Revision date: 06-01-2018 Issue date: 02-10-2014

97% of the mixture consists of component(s) of unknown acute oral toxicity. 100% of the mixture consists of component(s) of unknown acute dermal toxicity. 65% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 65% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Crystalline SiO2 (Quartz)		14808-60-7	60 - 100
Barium Sulfate		7727-43-7	15 - 40
Synthetic Amorphous Silica, Pptd.		112926-00-8	1 - 5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important Coughing. Prolonged exposure may cause chronic effects.

symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice General information (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Use water spray to cool unopened containers.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up Prevent product from entering drains. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR Components	ł 1910.1000) Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8)	TWA	0.8 mg/m3	
,		20 mppcf	
US. ACGIH Threshold Limit \ Components	Values Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
	TWA	0.05 mg/m3	Respirable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7) Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8)	TWA TWA	0.05 mg/m3 6 mg/m3	Respirable dust.
(CAS 14808-60-7) Synthetic Amorphous Silica,		6 mg/m3	Respirable dust.
(CAS 14808-60-7) Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8) ogical limit values	TWA	6 mg/m3 or the ingredient(s).	·
(CAS 14808-60-7) Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8)	TWA No biological exposure limits noted for Occupational exposure to nuisance of the control of	6 mg/m3 or the ingredient(s). dust (total and respirable) and respirable) and respirable, use process enclosustain airborne levels below reconstain airborne levels below reconstains.	espirable crystalline silica be used. Ventilation rates res, local exhaust ventilat mmended exposure limits
(CAS 14808-60-7) Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8) ogical limit values osure guidelines ropriate engineering trols	TWA No biological exposure limits noted to Occupational exposure to nuisance of should be monitored and controlled. Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been estable such as personal protective equipments.	6 mg/m3 or the ingredient(s). dust (total and respirable) and respirable, and respirable, and respirable, and respirable, use process enclosustain airborne levels below reconsished, maintain airborne levels nent	espirable crystalline silica be used. Ventilation rates res, local exhaust ventilat mmended exposure limits
(CAS 14808-60-7) Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8) ogical limit values osure guidelines ropriate engineering trols	TWA No biological exposure limits noted to Occupational exposure to nuisance of should be monitored and controlled. Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been estable	6 mg/m3 or the ingredient(s). dust (total and respirable) and respirable, and respirable, and respirable, and respirable, use process enclosustain airborne levels below reconsished, maintain airborne levels nent	espirable crystalline silica be used. Ventilation rates res, local exhaust ventilat mmended exposure limits

Material name: CWC 604 Machine Bond Aggregate

Other

SDS US GP113A Version #: 03 Revision date: 06-01-2018 Issue date: 02-10-2014

Use of an impervious apron is recommended.

Exposure Limit.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Sand Like
Physical state Solid.

Form Solid. Granular.
Color Natural color

Odor None.

Odor threshold Not available. pH Not available.

Melting point/freezing point 2876 °F (1580 °C) estimated

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

oer Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.00001 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density3.20 g/cm3Explosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

Specific gravity 3.2

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Powerful oxidizers. Aluminum. Chlorine. Phosphorus.

Material name: CWC 604 Machine Bond Aggregate

SDS US

Hazardous decomposition

No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Coughing.

Information on toxicological effects

Acute toxicity Not known.

Components Species **Test Results**

Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8)

Acute Oral

LD50 Rat > 22500 mg/kg

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

> inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial

circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in guarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

Known To Be Human Carcinogen.

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline SiO2 (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Synthetic Amorphous Silica, Pptd. (CAS 112926-00-8) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

Causes damage to organs through prolonged or repeated exposure.

repeated exposure

Aspiration hazard Not an aspiration hazard.

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D005: Waste Barium

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium Sulfate (CAS 7727-43-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

Cancer lung effects

iung enecis

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard Carcinogenicity

categories Specific target organ toxicity (single or repeated exposure)

Material name: CWC 604 Machine Bond Aggregate
GP113A Version #: 03 Revision date: 06-01-2018 Issue date: 02-10-2014

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to Crystalline SiO2 (Quartz), which is known to the State of California

to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

International Inventories

Taiwan

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Taiwan Chemical Substance Inventory (TCSI)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

02-10-2014 Issue date **Revision date** 06-01-2018

Version # 03

Health: 2 **HMIS®** ratings

Flammability: 0 Physical hazard: 0

Health: 2 NFPA ratings

Flammability: 0 Instability: 0

GP113A Version #: 03 Revision date: 06-01-2018 Issue date: 02-10-2014

Yes

Yes

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.