

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Ceramic Repair Putty Resin

Other means of identification
SKU# 0146

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street
Danvers, MA 01923
United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300
International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminium Oxide		1344-28-1	40 - 60
Epoxy Resin:--reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	EPOXY RESIN	25068-38-6	40 - 60
Xylene	XYLENE	1330-20-7	1 - 2.5
Ethyl Benzene		100-41-4	0.1 - 1
Other components below reportable levels			5 - 10

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminium Oxide (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Ethyl Benzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminium Oxide (CAS 1344-28-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminium Oxide (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Ethyl Benzene (CAS 100-41-4)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethyl Benzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
		TWA
Xylene (CAS 1330-20-7)	STEL	435 mg/m3
		100 ppm
	TWA	655 mg/m3
		435 mg/m3
		150 ppm
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethyl Benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Face shield is recommended.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Viscous. Liquid.
Physical state	Liquid.
Form	Viscous. Liquid.
Color	Amber.
Odor	Slight.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	608 °F (320 °C) estimated
Flash point	> 250.0 °F (> 121.1 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.14 g/cm ³ estimated
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.

Percent volatile	2.5 % estimated
Specific gravity	1.14 estimated
VOC	33 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Knowledge about health hazard is incomplete.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
------------	---------	--------------

Ethyl Benzene (CAS 100-41-4)

Acute

Dermal

LD50	Rabbit	17800 mg/kg
------	--------	-------------

Oral

LD50	Rat	3500 mg/kg
------	-----	------------

Xylene (CAS 1330-20-7)

Acute

Dermal

LD50	Rabbit	> 43 g/kg
------	--------	-----------

Inhalation

LC50	Rat	6350 mg/l, 4 Hours
------	-----	--------------------

Oral

LD50	Rat	3523 - 8600 mg/kg
------	-----	-------------------

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethyl Benzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	
Partition coefficient n-octanol / water (log Kow)	
Ethyl Benzene	3.15
Xylene	3.12 - 3.2
Mobility in soil	No data available.
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Aluminium Oxide (CAS 1344-28-1)	% 1.0
Ethyl Benzene (CAS 100-41-4)	% 0.1
Xylene (CAS 1330-20-7)	% 1.0

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Aluminium Oxide (CAS 1344-28-1)	Listed.
Ethyl Benzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

Toxic Substances Control Act (TSCA)**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethyl Benzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical

Classified hazard categories	Yes	Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitization
-------------------------------------	-----	---

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminium Oxide	1344-28-1	40 - 60
Ethyl Benzene	100-41-4	0.1 - 1
Xylene	1330-20-7	1 - 2.5

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethyl Benzene (CAS 100-41-4)	
Xylene (CAS 1330-20-7)	

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)	Contains component(s) regulated under the Safe Drinking Water Act.
---------------------------------------	--

US state regulations**California Proposition 65**

WARNING: This product can expose you to Ethyl Benzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl Benzene (CAS 100-41-4)	Listed: June 11, 2004
------------------------------	-----------------------

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethyl Benzene (CAS 100-41-4)	
Xylene (CAS 1330-20-7)	

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-28-2019
Revision date	04-29-2020
Version #	02
HMIS® ratings	Health: 2 Flammability: 1 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 1 Instability: 0
Disclaimer	ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.
Revision information	Composition/information on ingredients: Component information Accidental release measures: Methods and materials for containment and cleaning up Stability and reactivity: Conditions to avoid Toxicological information: Aspiration hazard Toxicological information: Corrosivity Toxicological information: Mutagenicity Toxicological information: Respiratory sensitization Toxicological information: Ingestion Toxicological information: Inhalation Toxicological information: Skin contact Toxicological information: Skin contact Toxicological information: Specific target organ toxicity - repeated exposure Toxicological information: Specific target organ toxicity - single exposure Transport information: General information

SAFETY DATA SHEET

1. Identification

Product identifier	DEVCON® Ceramic Repair Putty Hardener	
Other means of identification		
SKU#	5333N	
Recommended use	Not available.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	ITW Performance Polymers	
Address	30 Endicott Street Danvers, MA 01923 United States	
Telephone	Customer Service	978-777-1100
Website	www.itwperformancepolymers.com	
E-mail	Not available.	
Contact person	EHS Department	
Emergency phone number	Chemtrec	800-424-9300
	International	703-527-3887

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, dermal	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 2
	Specific target organ toxicity, single exposure	Category 1
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Formaldehyde, Oligomeric Reaction Products With Phenol And Triethylenetetramine	Formaldehyde, oligomeric reaction products with phenol and triethylenetetramine	32610-77-8	40 - 60
Phenol		108-95-2	10 - 20
TRIETHYLENETETRAMINE	TETA	112-24-3	10 - 20
Titanium Dioxide	TITANIUM DIOXIDE	13463-67-7	2.5 - 10
Benzyl Alcohol		100-51-6	1 - 2.5
Other components below reportable levels			10 - 20

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Phenol (CAS 108-95-2)	PEL	19 mg/m3	
		5 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
Phenol (CAS 108-95-2)	TWA	5 ppm
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Phenol (CAS 108-95-2)	Ceiling	60 mg/m3
		15.6 ppm
	TWA	19 mg/m3
		5 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Benzyl Alcohol (CAS 100-51-6)	TWA	44.2 mg/m3

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
		10 ppm
TRIETHYLENETETRAMIN E (CAS 112-24-3)	TWA	6 mg/m ³
		1 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Phenol (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Phenol (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US WEEL Guides: Skin designation

TRIETHYLENETETRAMINE (CAS 112-24-3) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Phenol (CAS 108-95-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Paste.
Physical state	Liquid.
Form	Paste.
Color	White.
Odor	Mild. Phenolic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	53.6 °F (12 °C) estimated

Initial boiling point and boiling range	359.15 °F (181.75 °C) estimated
Flash point	> 199.9 °F (> 93.3 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	3 % estimated
Flammability limit - upper (%)	10 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.27 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	640 °F (337.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.20 g/cm3 estimated
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Oxidizing properties	Not oxidizing.
Specific gravity	1.2 estimated
VOC	0 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Aluminum. Peroxides. Phenols.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs by inhalation. Prolonged inhalation may be harmful.
Skin contact	Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed.

Components	Species	Test Results
Benzyl Alcohol (CAS 100-51-6)		
Acute		
Dermal		
LD50	Rabbit	2000 mg/kg
Inhalation		
LC50	Rat	1000 mg/l, 8 Hours
Oral		
LD50	Rat	1230 - 3100 mg/kg
Phenol (CAS 108-95-2)		
Acute		
Dermal		
LD50	Rat	669 mg/kg
TRIETHYLENETETRAMINE (CAS 112-24-3)		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rat	1465 mg/kg
Oral		
<i>Liquid</i>		
LD50	Rat	1716 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	Suspected of causing genetic defects.	
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Phenol (CAS 108-95-2)	3 Not classifiable as to carcinogenicity to humans.	
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.	
Specific target organ toxicity - single exposure	Causes damage to organs.	
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.	
Chronic effects	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure.	

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
Benzyl Alcohol	1.1	
Phenol	1.46	
Mobility in soil	No data available.	

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Phenol (CAS 108-95-2) % 1.0

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Phenol (CAS 108-95-2) Listed.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Phenol (CAS 108-95-2) Listed.

SARA 304 Emergency release notification

PHENOL (CAS 108-95-2) 1000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Phenol	108-95-2	1000		500	10000

SARA 311/312 Hazardous chemical Yes

Classified hazard categories	Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation Respiratory or skin sensitization Germ cell mutagenicity Specific target organ toxicity (single or repeated exposure)
-------------------------------------	---

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Phenol	108-95-2	10 - 20

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Phenol (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Phenol (CAS 108-95-2) Low priority

US state regulations

California Proposition 65



WARNING: This product can expose you to Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Phenol (CAS 108-95-2)
Titanium Dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-28-2019
Revision date	04-29-2020
Version #	02
HMIS® ratings	Health: 3 Flammability: 1 Physical hazard: 0

NFPA ratings

Health: 3
Flammability: 1
Instability: 0

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Revision information

Composition/information on ingredients: Component information
Stability and reactivity: Conditions to avoid
Toxicological information: Aspiration hazard
Toxicological information: Carcinogenicity
Toxicological information: Mutagenicity
Toxicological information: Reproductivity
Toxicological information: Respiratory sensitization
Toxicological information: Skin contact
Toxicological information: Specific target organ toxicity - repeated exposure
Toxicological information: Specific target organ toxicity - single exposure