SAFETY DATA SHEET

1. Identification

Product identifier ITW Release Agent

Other means of identification

SKU# AI013E Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

ITW Performance Polymers Company name 130 Commerce Drive **Address** Montgomeryville, PA 18936

United States

Telephone Customer Service 215-855-8450

Website www.itwperformancepolymers.com

E-mail Not available. **EHS** Department **Contact person**

Emergency phone number CHEMTREC 800-424-9300

> International 703-527-3887

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2

> Gases under pressure Compressed gas

Serious eye damage/eye irritation Category 2B **Health hazards**

Environmental hazards Not classified. Not classified. **OSHA** defined hazards

Label elements



Signal word Warning

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. **Hazard statement**

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash thoroughly after handling.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and Response

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding Storage

50°C/122°F.

Dispose of waste and residues in accordance with local authority requirements. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 100% of the mixture consists of component(s) of unknown acute oral toxicity. 100% of the mixture

consists of component(s) of unknown acute dermal toxicity. 50% of the mixture consists of

component(s) of unknown acute inhalation toxicity. 100% of the mixture consists of component(s)

of unknown acute hazards to the aquatic environment. 100% of the mixture consists of

component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Material name: ITW Release Agent AI013E Version #: 09 Revision date: 06-19-2018 Issue date: 06-20-2013

Chemical name	Common name and synonyms	CAS number	%
DIMETHYL ETHER		115-10-6	30 - 60
Halogenated Hydrocarbon		75-37-6	30 - 60

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or

poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

During fire, gases hazardous to health may be formed.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Ingestion

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire fighting

equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed

General fire hazards

to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Material name: ITW Release Agent SDS US

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
DIMETHYL ETHER (CAS 115-10-6)	TWA	1880 mg/m3	
		1000 ppm	
Halogenated Hydrocarbon (CAS 75-37-6)	TWA	2700 mg/m3	
		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Aerosol.

Physical state Gas.

Form Aerosol. Compressed gas.

Color Clear water-white

Odor Ethereal
Odor threshold Not available.
pH Not available.

Material name: ITW Release Agent

Al013E Version #: 09 Revision date: 06-19-2018 Issue date: 06-20-2013

Not available. Melting point/freezing point Initial boiling point and boiling -13 °F (-25 °C)

range

Flash point Not available.

Evaporation rate 0 - 0.1

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. 4241 mm Hg Vapor pressure

Vapor density 1.91

Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

0.86 g/cm3 Density **Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

0.86 Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Causes eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

Information on toxicological effects

Not known. **Acute toxicity**

Components **Species Test Results**

DIMETHYL ETHER (CAS 115-10-6)

Acute Inhalation

LC50 Rat 164000 ppm, 4 Hours

Material name: ITW Release Agent SDS US 4/8 **Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes eve irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DIMETHYL ETHER 0.1 Halogenated Hydrocarbon 0.75

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name

Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)
Class 2.1

Subsidiary risk -Label(s) 2.1

Packing group Not available.

Material name: ITW Release Agent
Al013E Version #: 09 Revision date: 06-19-2018 Issue date: 06-20-2013

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 Packaging exceptions 306 Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN number**

Aerosols, flammable **UN proper shipping name**

Transport hazard class(es)

Class 2.1 Subsidiary risk

Not available. Packing group

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950 **AEROSOLS UN** proper shipping name

Transport hazard class(es) Class 2 Subsidiary risk

Packing group Not available.

Environmental hazards

Marine pollutant No. **EmS** F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT







Material name: ITW Release Agent Al013E Version #: 09 Revision date: 06-19-2018 Issue date: 06-20-2013

General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

DIMETHYL ETHER (CAS 115-10-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Gas under pressure categories

Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

DIMETHYL ETHER (CAS 115-10-6) Halogenated Hydrocarbon (CAS 75-37-6) Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: ITW Release Agent

SDS US

AI013E Version #: 09 Revision date: 06-19-2018 Issue date: 06-20-2013

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Vo

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 06-20-2013

 Revision date
 06-19-2018

Version # 09

HMIS® ratings Health: 1

Flammability: 2 Physical hazard: 1

NFPA ratings Health: 1

Flammability: 2 Instability: 1

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: ITW Release Agent SDS US