SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Plastic Steel® Putty (A) Resin

Other means of identification

SKU# 0100

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Sensitization, skin Category 1

Specific target organ toxicity following single Category 3 narcotic effects

exposure

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

cause drowsiness or dizziness.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only

outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the

workplace. Wear eye protection/face protection. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep

comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists:

Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
FERROSILICON		8049-17-0	60 - 100
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	Epoxy resin	25068-38-6	10 - 30
FIBROUS GLASS		65997-17-3	0.1 - 1
Other components below reportable	levels		1 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed
General information

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

protect themselves. Wash contaminated clothing before reuse.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

General fire hazards

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good

industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

5 mg/m3

8. Exposure controls/personal protection

Occu	national	exposure	limite
Occu	pationai	exposure	111111111111111111111111111111111111111

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)					
Components	Туре	Value	Form		
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.2 fibers/cm3	Fiber.		
		5 mg/m3	Total particulate.		

Canada, British Columbia OELs, (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form	
FIBROUS GLASS (CAS	TWA	0.2 fibers/cm3	Fiber.	
65007 17 2)				

65997-17-3)

5 mg/m3 Inhalable fibers.

Fiber, total

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	5 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form	
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.5 fibers/ml	Respirable fibers.	
,		5 mg/m3	Inhalable fraction.	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components **Form**

	.) 0	1 4.14.0	_	
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/cm3n	Fiber.	
		10 mg/m3	fibers, total dust	

Conada Saakatahawan AELa (Asaunational Haalth and Safaty Bagulationa, 1006, Table 21)

Components	Type	Value	Form	
FIBROUS GLASS (CAS 65997-17-3)	15 minute	10 mg/m3	Inhalable fraction.	
	8 hour	0.2 fibers/cc	Respirable fibers.	
		5 mg/m3	Inhalable fraction.	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Appropriate engineering controls

Occupational Exposure Limits are not relevant to the current physical form of the product.

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. **Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance Paste.

Physical stateNot available.FormPaste.ColourDark greyOdourSlight.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

320 °C (608 °F) estimated

Flash point > 204.0 °C (> 399.2 °F) Pensky-Martens Closed Cup

Evaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water)

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 2.80 g/cm3 **Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 2.8

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidising agents.

Material name: DEVCON® Plastic Steel® Putty (A) Resin 0100 Version #: 01 Issue date: 01-May-2020

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Knowledge about health hazard is incomplete.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

FIBROUS GLASS (CAS 65997-17-3) Irritant

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

ACGIH Carcinogens

FIBROUS GLASS (CAS 65997-17-3)

A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

FIBROUS GLASS (CAS 65997-17-3) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

FIBROUS GLASS (CAS 65997-17-3) Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

FIBROUS GLASS (CAS 65997-17-3) Detected carcinogenic effect in animals.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: DEVCON® Plastic Steel® Putty (A) Resin 0100 Version #: 01 Issue date: 01-May-2020

SDS CANADA

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established. Not applicable.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

FIBROUS GLASS (CAS 65997-17-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: DEVCON® Plastic Steel® Putty (A) Resin

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

01-May-2020 Issue date

Version No. 01

ITW Performance Polymers cannot anticipate all conditions under which this information and its Disclaimer

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

0100 Version #: 01 Issue date: 01-May-2020

Material name: DEVCON® Plastic Steel® Putty (A) Resin SDS CANADA 7/7

SAFETY DATA SHEET

1. Identification

Product identifier Putty Hardener

Other means of identification

SKU# 0200C

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, dermal

Skin corrosion/irritation

Serious eye damage/eye irritation

Category 2

Category 1

Sensitization, skin

Category 1

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Harmful if swallowed. Harmful in contact with skin. Causes skin irritation. May cause an allergic

skin reaction. Causes serious eye damage.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat,

drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves/protective clothing.

Response IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth. IF ON SKIN:

Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

Material name: Putty Hardener SDS CANADA

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aliphatic Amines		N/A	30 - 60
Benzyl alcohol		100-51-6	15 - 40
TRIETHYLENETETRAMINE	TETA	112-24-3	15 - 40
Silica, amorphous, fumed	Silica, amorphous, fumed, crystfree	112945-52-5	7 - 13
Titanium dioxide	Titanium dioxide	13463-67-7	0.5 - 1.5
Other components below reporta	ble levels		0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. Get medical Skin contact advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical

attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water spray. Alcohol resistant foam. Powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use water spray to cool unopened containers.

Specific methods General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Material name: Putty Hardener SDS CANADA

Avoid discharge into drains, water courses or onto the ground.

0200C Version #: 05 Revision date: 12-January-2021 Issue date: 03-July-2019

7. Handling and storage

Precautions for safe handling

Do not get this material in contact with eyes. Do not taste or swallow. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH	Threshold	Limit Values
-----------	-----------	---------------------

Components	Туре	Value
Titanium dioxide (CAS	TWA	10 mg/m3

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
,		10 mg/m3	Total dust.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	
Titanium dioxide (CAS	TWA	10 mg/m3	
13463-67-7)			

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
TRIETHYLENETETRAMIN E (CAS 112-24-3)	TWA	3 mg/m3	
		0.5 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Туре	Value	Form
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational Exposure Limits are not relevant to the current physical form of the product.

Canada - Ontario OELs: Skin designation

TRIETHYLENETETRAMINE (CAS 112-24-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Material name: Putty Hardener SDS CANADA

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles) and a face shield. Face shield is Eye/face protection

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Keep away from food and drink, Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Paste. **Physical state** Solid. **Form** Paste. White Colour

Ammoniacal. Odour Not available. **Odour threshold** Not available. pН

-15.2 °C (4.64 °F) estimated Melting point/freezing point Initial boiling point and boiling 216 °C (420.8 °F) estimated

range

> 93.3 °C (> 199.9 °F) Flash point

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper Not available.

(%)

Vapour pressure 5.73 hPa estimated

Vapour density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

337.78 °C (640 °F) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 1.00 g/cm3 estimated

Not explosive. **Explosive properties Oxidising properties** Not oxidising. 1 estimated Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport. Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

flash point. Contact with incompatible materials.

Incompatible materials Peroxides. Phenols.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed.

Components Species Test Results

Benzyl alcohol (CAS 100-51-6)

Acute Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat 1000 mg/l, 8 Hours

Silica, amorphous, fumed (CAS 112945-52-5)

Acute Oral

LD50 Rat > 22500 mg/kg

TRIETHYLENETETRAMINE (CAS 112-24-3)

Acute Dermal

Liquid

LD50 Rat 1465 mg/kg

Oral *Liquid*

LD50 Rat 1716 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Titanium dioxide (CAS 13463-67-7) Irritant

Respiratory sensitisation Not a respiratory sensitizer.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Titanium dioxide (CAS 13463-67-7)

A4 Not classifiable as a human carcinogen.

Material name: Putty Hardener SDS CANADA

Canada - Manitoba OELs: carcinogenicity

Titanium dioxide (CAS 13463-67-7)

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica, amorphous, fumed (CAS 112945-52-5)

3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzyl alcohol 1.1

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not applicable.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

Material name: Putty Hardener SDS CANADA

0200C Version #: 05 Revision date: 12-January-2021 Issue date: 03-July-2019

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) Yes Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information

Issue date 03-July-2019 **Revision date** 12-January-2021

Version No. 05

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or

in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

Material name: Putty Hardener SDS CANADA

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).