

1. Identification		
Product identifier		
Product name	CHOCKFAST RED SG RESIN	
Product number	Y0007	
Recommended use of the ch	Recommended use of the chemical and restrictions on use	
Application	Resin. Pourable Casting Compound When Mixed With Hardener And Aggregate	
Details of the supplier of the	safety data sheet	
Supplier		
	ITW Performance Polymers	
	Bay 150	
	Shannon Industrial Estate	
	Co. Clare	
	Ireland	
	V14 DF82	
	353(61)771500	
	353(61)471285	
	mail@itwpp.com	
Emergency telephone number		
Emergency telephone	+44(0)1235 239 670 (24h)	
2. Hazard(s) identification		
Classification of the substance	ce or mixture	
Physical hazards	Not Classified	
Health hazards	Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317	
Environmental hazards	Aquatic Chronic 2 - H411	
Human health	The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.	
Label elements		
Pictogram		
	¥2	
Signal word	Danger	
Hazard statements	H315 Causes skin irritation.	

H411 Toxic to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

Precautionary statements	 P261 Avoid breathing vapor/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing must not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 If on skin: Wash with plenty of water. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a poison center/ doctor. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
	P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P501 Dispose of contents/ container in accordance with national regulations.
Contains	EPOXY RESIN (Number average MW <= 700), 1,4-BIS[(2,3- EPOXYPROPOXY)METHYL]CYCLOHEXANE, GAMMA-BUTYROLACTONE

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

EPOXY RESIN (Number average MW <= 700)

CAS number: 25068-38-6

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE

CAS number: 14228-73-0

Classification

Skin Sens. 1 - H317

GAMMA-BUTYROLACTONE

CAS number: 96-48-0

Classification

Acute Tox. 4 - H302 Eye Dam. 1 - H318 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

10-30%

60-100%

5-10%

General information	Avoid contact with skin and eyes. Show this safety data sheet to the doctor in attendance
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
Skin Contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.
Most important symptoms and	effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Indication of immediate medica	al attention and special treatment needed
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
5. Fire-fighting measures	
Extinguishing media	
Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Special hazards arising from the	he substance or mixture
Specific hazards	Irritating gases or vapors.
Advice for firefighters	
Protective actions during firefighting	Avoid breathing fire gases or vapors. Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
6. Accidental release measure	S
Personal precautions, protectiv	ve equipment and emergency procedures
Personal precautions	Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.
Environmental precautions	
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
Methods and material for conta	ainment and cleaning up
Methods for cleaning up	Absorb spillage with sand or other inert absorbent. Transfer to covered steel drums for disposal. Containers with collected spillage must be properly labeled with correct contents and hazard symbol.
Deference to other coeffere	Wear protective clothing as described in Section 8 of this safety data sheet.
Reference to other sections	wear protective clothing as described in Section of this safety data sheet.
7. Handling and storage	

Usage precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Use only in well- ventilated areas. Keep away from heat, sparks and open flame. Open drum carefully as content may be under pressure. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated.
Conditions for safe storage, in	ncluding any incompatibilities
Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).
Specific end uses(s)	

Specific end use(s)

The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Exposure controls

Protective equipment









Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Use approved respirator if air contamination is above an acceptable level. Ensure operatives are trained to minimize exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with OSHA 1910.133.
Hand protection	Wear protective gloves made of the following material: Rubber or plastic. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. It is recommended that gloves are made of the following material: Butyl rubber. Laminate of polyethylene and ethylene vinyl alcohol (PE/EVOH). Neoprene. Frequent changes are recommended. The selected gloves should have a breakthrough time of at least 6 hours.
Other skin and body protection	Wear apron or protective clothing in case of contact.
Hygiene measures	Provide eyewash station and safety shower. Keep away from food, drink and animal feeding

stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

 Respiratory protection
 If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved.

9. Physical and Chemical Prop	perties
Information on basic physical and chemical properties	
Appearance	Viscous liquid.
Color	Colorless to pale yellow.
Odor	Slight.
рН	pH (concentrated solution): 11.1 @ 20 °C
Melting point	<5, >-15°C
Initial boiling point and range	>200°C @
Flash point	> 93°C
Relative density	1.1 - 1.18 @ @ 20 °C°C
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	>300°C
Other information	Not available.
10. Stability and reactivity	
Reactivity	Acids. Amines. Strong oxidizing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Not available.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.
Materials to avoid	Avoid contact with the following materials: Strong acids. Alkalis - inorganic. Alkalis - organic. Strong oxidizing agents. Amines.
Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Acids - organic. Aldehydes.
11. Toxicological information	
Information on toxicological eff	fects
Acute toxicity - oral ATE oral (mg/kg)	8,000.0
Skin Contact	Irritating to skin. May cause sensitisation by skin contact. May cause sensitization or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.
Route of entry	Inhalation Ingestion.
12. Ecological Information	

Ecotoxicity	Avoid releasing into the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
Toxicity	Very toxic to aquatic organisms.
Persistence and degradability	
Persistence and degradability	There are no data on the degradability of this product.
Bioaccumulative potential	
Bio-Accumulative Potential	No data available on bioaccumulation.
Mobility in soil	
Mobility	Do not discharge into drains or watercourses or onto the ground.
Other adverse effects	
Other adverse effects	Not available.
13. Disposal considerations	
Waste treatment methods	
General information	When handling waste, the safety precautions applying to handling of the product should be considered.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 99
14. Transport information	
UN Number	
	3082
UN Number	3082 3082
<u>UN Number</u> UN No. (TDG)	
UN Number UN No. (TDG) UN No. (IMDG)	3082
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO)	3082 3082
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO) UN No. (DOT)	3082 3082
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO) UN No. (DOT) UN proper shipping name	3082 3082 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO) UN No. (DOT) <u>UN proper shipping name</u> Proper shipping name (TDG)	3082 3082 3082 BNVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO) UN No. (DOT) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG)	3082 3082 3082 BENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO) UN No. (DOT) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG) Proper shipping name (ICAO)	3082 3082 3082 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO) UN No. (ICAO) UN No. (DOT) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG) Proper shipping name (ICAO)	3082 3082 3082 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
UN Number UN No. (TDG) UN No. (IMDG) UN No. (ICAO) UN No. (ICAO) UN No. (DOT) <u>UN proper shipping name</u> Proper shipping name (TDG) Proper shipping name (IMDG) Proper shipping name (ICAO) Proper shipping name (DOT) <u>Transport hazard class(es)</u>	3082 3082 3082 BENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))

ICAO class/division

Transport labels



Packing group

TDG Packing Group	III
IMDG packing group	111
ICAO packing group	III
DOT packing group	

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS

F-A, S-F

9

15. Regulatory information	
16. Other information	
Revision date	4/6/2018
Revision	10
Supersedes date	4/20/2015
Hazard statements in full	 H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.