

PHILLYMASTIC TG-7B PASTE RESIN

1. Identification	1. Identification	
Product identifier		
Product name	PHILLYMASTIC TG-7B PASTE RESIN	
Product number	Y0013	
Recommended use of the chemical and restrictions on use		
Application	Resin.	
Details of the supplier of the s	afety data sheet	
Supplier		
	ITW Performance Polymers	
	Bay 150	
	Shannon Industrial Estate	
	Co. Clare	
	Ireland	
	V14 DF82	
	353(61)771500	
	353(61)471285	
	mail@itwpp.com	
Emergency telephone number	<u>r</u>	
Emergency telephone	+44(0)1235 239 670 (24h)	
2. Hazard(s) identification		
Classification of the substance	e or mixture	
Physical hazards	Not Classified	
Health hazards	Skin Irrit. 2 - H315 Skin Sens. 1 - H317	
Environmental hazards	Aquatic Chronic 2 - H411	
Human health	The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.	
Label elements		
Pictogram		
Signal word	Warning	
Hazard statements	H315 Causes skin irritation.	
	H317 May cause an allergic skin reaction.	
	H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.	

Precautionary statements	<ul> <li>P261 Avoid breathing vapor/ spray.</li> <li>P264 Wash contaminated skin thoroughly after handling.</li> <li>P272 Contaminated work clothing must not be allowed out of the workplace.</li> <li>P273 Avoid release to the environment.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> <li>P302+P352 If on skin: Wash with plenty of water.</li> <li>P321 Specific treatment (see medical advice on this label).</li> <li>P332+P313 If skin irritation occurs: Get medical advice/ attention.</li> <li>P362+P364 Take off contaminated clothing and wash it before reuse.</li> <li>P391 Collect spillage.</li> <li>P501 Dispose of contents/ container in accordance with national regulations.</li> </ul>
Contains	EPOXY RESIN (Number average MW <= 700 )

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

## 3. Composition/information on ingredients

### Mixtures

CAS number: 25068-38-6

### Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

## **FIBROUS GLASS**

CAS number: 65997-17-3

### Classification

Carc. 1B - H350

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures	
Description of first aid measures	
General information	Show this safety data sheet to the doctor in attendance Avoid contact with skin and eyes.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
Skin Contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

### Most important symptoms and effects, both acute and delayed

10-30%

30-60%

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.	
Indication of immediate medica	Indication of immediate medical attention and special treatment needed	
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.	
5. Fire-fighting measures		
Extinguishing media		
Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.	
Special hazards arising from the	he substance or mixture	
Specific hazards	Irritating gases or vapors.	
Advice for firefighters		
Protective actions during firefighting	Avoid breathing fire gases or vapors. Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.	
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.	
6. Accidental release measure	15	
Personal precautions, protectiv	ve equipment and emergency procedures	
Personal precautions	Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.	
Environmental precautions		
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.	
Methods and material for conta	ainment and cleaning up	
Methods for cleaning up	Absorb spillage with sand or other inert absorbent. Transfer to covered steel drums for disposal. Containers with collected spillage must be properly labeled with correct contents and hazard symbol.	
Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet.	
7. Handling and storage		
Precautions for safe handling		
Usage precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Use only in well- ventilated areas. Keep away from heat, sparks and open flame. Open drum carefully as content may be under pressure. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.	
Conditions for safe storage, in	cluding any incompatibilities	
Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).	
Specific end uses(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.	
8. Exposure Controls/personal protection		

Ingredient comments

No exposure limits known for ingredient(s).

#### Exposure controls

Protective equipment



Appropriate engineering

controls



Provide adequate general and local exhaust ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Hand protection Wear protective gloves made of the following material: Rubber or plastic. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. The selected gloves should have a breakthrough time of at least 8 hours. Other skin and body Wear apron or protective clothing in case of contact. protection Hygiene measures Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace. **Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter

mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

#### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

Appearance	Viscous liquid.
Color	White/off-white.
Odor	Aromatic.
рН	pH (concentrated solution): 7 @ 25 °C
Initial boiling point and range	277°C @
Flash point	>171°C
Vapor pressure	<0.03 mmHg @ °C
Relative density	1.75 @ 20 °C°C
Solubility(ies)	Slightly soluble in water.
Auto-ignition temperature	>300°C
Other information	Not available.

## 10. Stability and reactivity

Reactivity	Strong oxidizing agents. Acids. Amines.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Not available.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.
Materials to avoid	Avoid contact with the following materials: Strong oxidizing agents. Strong acids. Amines.
Hazardous decomposition products	Fire or high temperatures create: Nitrous gases (NOx). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO2). Vapours/gases/fumes of: Ammonia or amines.
11. Toxicological information	

## Information on toxicological effects

Skin Contact	Irritating to skin. May cause sensitisation by skin contact. Prolonged contact may cause redness, irritation and dry skin. The product contains a small amount of sensitizing substance. May cause sensitization or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.
Route of entry	Inhalation Ingestion.
12. Ecological Information	
Ecotoxicity	Avoid release to the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.
Toxicity	Very toxic to aquatic organisms.
Persistence and degradability Persistence and degradability Bioaccumulative potential	There are no data on the degradability of this product.
Bio-Accumulative Potential	No data available on bioaccumulation.
<u>Mobility in soil</u> Mobility	Do not discharge into drains or watercourses or onto the ground.
Other adverse effects	Not available.
Other adverse effects	NOT AVAIIADIE.
13. Disposal considerations	
Waste treatment methods	
General information	When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 99
14. Transport information	
General	No other information known.
UN Number	
UN No. (TDG)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (DOT)	3082
UN proper shipping name	
Proper shipping name (TDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))
Proper shipping name (DOT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))
Transport hazard class(es)	
TDG class	9
TDG label(s)	9
IMDG Class	9
ICAO class/division	9
Transport labels	
9	
Packing group	
TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III
Environmental hazards	
Environmentally Hazardous Su	ubstance

Special precautions for user

EmS

F-A, S-F

Transport in bulk according to No information required. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information	
16. Other information	
Revision date	4/6/2018
Revision	10
Supersedes date	2/13/2018
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H350 May cause cancer. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.