



**SAFETY DATA SHEET
CHOCKFAST BLACK RESIN.**

1. Identification

Product identifier

Product name CHOCKFAST BLACK RESIN.

Product number Y0005

Recommended use of the chemical and restrictions on use

Application Resin.

Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers
Bay 150
Shannon Industrial Estate
Co. Clare
Ireland
V14 DF82
353(61)771500
353(61)471285
mail@itwpp.com

Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

Human health The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.

Label elements

Pictogram



Signal word

Warning

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

CHOCKFAST BLACK RESIN.

Precautionary statements	<p>P261 Avoid breathing vapor/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing must not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 If on skin: Wash with plenty of water.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	--

Contains	EPOXY RESIN (Number average MW <= 700), 1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE
-----------------	---

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

EPOXY RESIN (Number average MW <= 700)	10-30%
CAS number: 25068-38-6	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	1-5%
CAS number: 14228-73-0	
Classification	
Skin Sens. 1 - H317	
GAMMA-BUTYROLACTONE	1-5%
CAS number: 96-48-0	
Classification	
Acute Tox. 4 - H302	
Eye Dam. 1 - H318	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

CHOCKFAST BLACK RESIN.

General information	Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Inhalation	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
Skin Contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

Indication of immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

Special hazards arising from the substance or mixture

Specific hazards	Irritating gases or vapors.
-------------------------	-----------------------------

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors. Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.
---	--

Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.
-----------------------------	---

Environmental precautions

Environmental precautions	Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for cleaning up	Absorb spillage with sand or other inert absorbent. Transfer to covered steel drums for disposal. Containers with collected spillage must be properly labeled with correct contents and hazard symbol.
--------------------------------	--

Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet.
------------------------------------	---

7. Handling and storage

CHOCKFAST BLACK RESIN.

Precautions for safe handling

Usage precautions

Use only in well-ventilated areas. Keep away from heat, sparks and open flame. Open drum carefully as content may be under pressure. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Specific end uses(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Ingredient comments

No exposure limits known for ingredient(s).

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Rubber or plastic.

Other skin and body protection

Wear chemical protective suit.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance

Viscous liquid.

Color

Black.

Odor

No characteristic odor.

pH

pH (concentrated solution): 7 @ 20 °C

Initial boiling point and range

277°C @

Flash point

> 254°C

Relative density

1.70 @ 20 °C

Solubility(ies)

Slightly soluble in water.

Auto-ignition temperature

>300°C

CHOCKFAST BLACK RESIN.

Other information Not available.

10. Stability and reactivity

Reactivity Strong oxidizing agents. Amines. Acids.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous reactions Not available.

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.

Materials to avoid Avoid contact with the following materials: Strong oxidizing agents. Strong acids. Amines.

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Acids - organic. Aldehydes.

11. Toxicological information**Information on toxicological effects****Acute toxicity - oral**

ATE oral (mg/kg) 48,543.69

Skin Contact Irritating to skin. May cause sensitization or allergic reactions in sensitive individuals. Repeated exposure may cause skin dryness or cracking.

Eye contact Irritating to eyes.

Acute and chronic health hazards The product contains an epoxy resin. May cause sensitization or allergic reactions in sensitive individuals.

12. Ecological Information

Ecotoxicity Avoid releasing into the environment. The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Toxicity Not considered toxic to fish.

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Mobility in soil

Mobility Do not discharge into drains or watercourses or onto the ground.

Other adverse effects

Other adverse effects Not available.

13. Disposal considerations**Waste treatment methods**

CHOCKFAST BLACK RESIN.

General information	When handling waste, the safety precautions applying to handling of the product should be considered.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 99

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

No information required.

UN proper shipping name

No information required.

Transport hazard class(es)

Transport labels

No transport warning sign required.

Packing group

No information required.

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

No information required.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

15. Regulatory information

16. Other information

Revision date	4/5/2018
Revision	10
Supersedes date	4/23/2015
Hazard statements in full	H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

CHOCKFAST BLACK RESIN.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.